

BrewWISE® Single Soft Heat® DBC Brewer

ITEM#

PROJECT

DATE

Features

BrewWISE® Brewing System

- Brews ½, 1, or 1½ gallon (1.9, 3.8 or 5.7 litre) batches.
- Stores individual coffee and flavor profiles using adjustable water volume, bypass percentage, pulse brew and pre-infusion timing.
- Operate any combination of BrewWISE® equipment error-free with wireless brewer-grinder interface via Smart Funnel®.
- Reduce accidents with safety features that decrease hot splashes from funnel, eliminate brewing when funnel or server is not present.
- Troubleshoot all switches and electrical components from the front panel with advanced diagnostic service tools.
- Consistently brew perfect coffee using Digital Brewer Control with BUNN patented pulse brew.
- Brewers use patented SH servers, sold separately, with heat control with auto shut off once target temperature is reached.
- Simplify installation and calibration by creating your own recipe cards and dedicated funnels with the BrewWISE Recipe Writer using your PC (U.S. and English Windows® compatible).
- Brew capacity varies by model. See back for details.



Single SH DBC with SH Server

(servers sold separately)

Dimensions: 35.8" H x 9.3" W x 23.1" D
(90.9cm H x 23.6cm W x 58.7cm D)

For current specification sheets and other information, go to www.bunn.com.

International models may vary in appearance.

Related Products

Easy Clear® EQHP-10
Product No. : 39000.0004



Easy Clear® EQHP-10L
Product No. : 39000.0001

Single/Dual Filter Pack
Product No. : 20138.0000



BrewWISE® Recipe Writer (BRW)




Recipe Card
Product No.: 34447.0000

- Program a recipe to be used on brewer or grinder.



Ad Card
Product No.: 34448.0000

- Program a message to appear on the brewer's display.






G9-2T DBC



One Position Drip Tray
For use with Single/Single SH
Product No.: 26830.0000



Dimensions & Specifications

Model	Product #	Volts	Amps	Tank Heater Watts	Total Watts	Capacity	Shipping Weight	Cord Attached	Agency
Single SH DBC	33600.0003	230	16.2	3500	3723	10.6 gal./hr. (40.1 L/hr)	59 lbs. (26.8 kg)	No	CE  
Single SH DBC	33600.0005	200	19	3500	3800	10.6 gal./hr. (40.1 L/hr)	59 lbs. (26.8 kg)	No	
Single SH DBC	33600.0012	220	12.7	3500	2800	10.6 gal./hr. (40.1 L/hr)	59 lbs. (26.8 kg)	No	

Note: Soft Heat® Brewers and Servers are sold, boxed and shipped separately.

Brewing capacity: based upon incoming water temp of 60°F/15.5°C (140°F/60°C rise).

Equipped with funnel locks.

Electrical: 230 volt model requires 2-wires plus ground service rated 220-240V, single phase, 50/60Hz.

220 volt model requires 2-wires plus ground service rated 220-240V, single phase, 60Hz.

200 volt model requires 2-wires plus ground service, single phase, 50Hz.

Plumbing: 20-90 psi (138-621 kPa). Machine supplied with ¼" male fitting.

