

Technical Data for CE Marked Products

Nominal Heat Input: (Net)	Natural (I_{2H}) = 21.1 KW (72,000 Btu/h) Natural (I_{2E}) = 21.1 KW (72,000 Btu/h) Natural (I_{2E+}) = 21.1 KW (72,000 Btu/h) Natural (I_{2L}) = 21.1 KW (72,000 Btu/h) Liquid Propane (I_{3p}) = 21.1 KW (72,000 Btu/h)
Nominal Heat Input: (Gross)	Natural (I_{2H}) = 23.4 KW (80,000 Btu/h) Natural (I_{2E}) = 23.4 KW (80,000 Btu/h) Natural (I_{2E+}) = 23.4 KW (80,000 Btu/h) Natural (I_{2L}) = 23.4 KW (80,000 Btu/h) Liquid Propane (I_{3p}) = 22.9 KW (78,000 Btu/h)
Supply Pressure:	Natural (I_{2H}) = 20 mbar Natural (I_{2E}) = 20 mbar Natural (I_{2E+}) = 20/25 mbar Natural (I_{2L}) = 25 mbar Liquid Propane (I_{3p}) = 30 mbar Liquid Propane (I_{3p}) = 37 mbar Liquid Propane (I_{3p}) = 50 mbar
Test Point Pressure:	Natural (I_{2H}) = 8.7 mbar Natural (I_{2E}) = 8.7 mbar Natural (I_{2E+}) = 8.7/10 mbar Natural (I_{2L}) = 10 mbar Liquid Propane (I_{3p}) = 25 mbar
Injector Size:	Natural (I_{2H}) = 1.04 mm Natural (I_{2E}) = 1.04 mm Natural (I_{2E+}) = 1.04 mm Natural (I_{2L}) = 1.04 mm Liquid Propane (I_{3p}) = 0.66 mm
Restrictor Size:	Natural (I_{2E+}) = 4.1 mm

This appliance must be installed in accordance with the manufacturer's instructions and the regulations in force and only used in a suitably ventilated location. Read the instructions fully before installing or using the appliance.