

SECTION 2. INSTALLATION

2-1. INTRODUCTION

NOTICE

Installation of this unit should be performed only by qualified service personnel.



Do not puncture the skin of unit with drills or screws as component damage or electrical shock could result.

2-2. UNPACKING

The Henny Penny Heated Holding Cabinet has been inspected, tested, and packed to ensure arrival in the best possible condition. The cabinet is packed inside a triple wall carton with sufficient packing material to withstand normal handling in shipment. The carton is also strapped onto a wooden base.

NOTICE

Any shipping damages should be noted in the presence of the delivery agent and signed prior to his or her departure.

To remove the cabinet from its carton:

1. Cut the bands holding the wooden base to the carton.
2. Lift the carton off the cabinet.
3. Remove unit from the wooden base.
4. Remove all packing material from around cabinet and inside drawers.
5. Peel off protective covering from exterior of cabinet.

Your heated holding cabinet is now ready to be located and installed.

2-3. LOCATION

The unit should be placed on a table or shelf to allow easy access for loading and unloading of product. For proper operation, the cabinet must be level.

2-4. ELECTRICAL CONNECTION

The heated holding cabinet is available from the factory as a 120 VAC, 50/60 Hz, or 230 VAC, 50 Hz, single-phase unit. The data plate on the back of the unit specifies the correct electrical supply. The unit requires a grounded receptacle with a separate electrical line protected by a fuse or circuit breaker of the proper rating.



To avoid electrical shock, the cabinet must be adequately and safely grounded (earthed) according to local electrical codes.

(FOR EQUIPMENT WITH CE MARK ONLY!)

To prevent electric shock hazard this appliance must be bonded to other appliances or touchable metal surfaces in close proximity to this appliance with an equipotential bonding conductor. This appliance is equipped with an equipotential lug for this purpose. The equipotential lug is marked with the following symbol



<u>Model Number</u>	<u>Volts</u>	<u>Watts</u>	<u>Amps</u>
HCD-930/932	120	846	7
HCD-930/932	230	846	3.6

2-5. PHYSICAL SPECIFICATIONS

- 46 cm. wide x 64 cm. deep x 53 cm. high (18" x 24" x 21")
- 46 cm. wide x 64 cm. deep x 42 cm. high (18" x 24" x 16")
- HCD-930 – Shipping weight – 62.7 kg. (138 pounds)
- HCD-932 – Shipping weight – 60.7 kg. (134 pounds)