SERVICE INSTRUCTIONS

Part No. 037247

www.keatingofchicago.com



1-800-KEATING


GAS VALVE 24V Replacement Kit for BB & TS Spark Ignition Units (No Filter)

Part # 037239 (replaces 033156) (NG) & 037240 (replaces 035007) (LP)

What's included in your package?

- Replacement Gas Valve
- Replacement Pilot Tubing
- Additional Relay DPDT 24V AC
- Wiring Harness

Replacement Gas Valve



Installation Instructions

- 1. Open control panel and detach it from fryer cabinet.
- 2. Install the relay assembly with provided hardware to matching holes on control panel back.
- 3. Attach control panel to fryer cabinet.
- 4. Cut wire #25 from connector on common prong of High Limit Test Switch and remove it. Cut wire #53 from connector on left side prong of High Limit Test Switch and remove it with wire #24 together.
- 5. Connect wires drawn with thicker lines on the diagram as shown using attached connectors. Be sure yellow wire between thermostat and left prong on push to light switch is connected.

NOTE: Pink or blue connectors go to the relay as shown below

- 6. Close control panel.
- 7. Test fryer.

See Reverse for Wiring Instructions

7/03 #037247

Wiring Instructions for Ready to Cook Light Relay on BBSI & TSSI Units

