

GLASSLINED TANK FEATURES

"Glasslining," a porcelain protective coating to a steel tank interior, is the plumbing industry's most time-tested system for protection of tanks. A. O. Smith Glasslined Pump Tanks feature rolled-steel construction, and every A. O. Smith Tank is made in the U.S.A.

Other A. O. Smith features include a 1-1/4" NPT spud on top for motor mount or retention tank connections, a 1/4" switch or gauge tapping on the air side of the tank, and full-size 1-1/4" connections at all needed locations.

ROLLED STEEL CONSTRUCTION

- Provides added structural strength and more capacity within the same diameters.

FUSED GLASSLINING

MAXIMUM WORKING PRESSURE 100 PSIG

3-YEAR LIMITED WARRANTY

EXTERIOR POWDER COAT

- Excellent resistance to UV rays



G Series Glasslined Pump Tanks

Model Number	Volume (Gal)	Dimensions in Inches						Weight (Lbs)
		A	B	C	D	E	F	
SGT-42	42	49	26-3/8	16-1/2	12-3/8	3-1/8	6	77
SGS-42	42	35-7/8	17-3/8	20	8-3/8	3-1/8	6	79
SG-82	82	62-1/4	33-3/8	20	12-3/8	3-1/8	6	120
SG-120	120	63	33-3/8	24	12-3/8	3-1/8	6	160
SG-220	220	62	38	36	12	7	6	640



