Item No.

# Built To Anets Standards, Priced For Today's Market

Anets provides the highest value in frying with the new SLG100 18" gas fryer. Ideal for both batch cooking and large volumes load after load. The heating system has been engineered for maximum efficiency and cleanability. To achieve optimum cooking capacity this fryer requires only 150,000 BTU input, using 4 burner tubes equipped with computer designed radiants. Higher BTUs for fast recovery and rapid oil heat up result in limited oil absorption and great tasting food. Center mounted snap action thermostat responds quickly to fry loads. The Anets SLG100 is built to perform, easy to clean and priced to purchase today.

### STANDARD FEATURES

- Pulse Ignitor (No electrical required)
- Stainless steel front, door and trim are standard features
- 150,000 BTUH from only four tubes, easiest model on the market to clean
- Computer designed radiants enable the burners to efficiently reach 37,500 BTUH per burner tube
- The unique tapered elliptical tubes provide 14% more heat transfer area than competitive models (see **Design Features** on back)
- Outstanding serviceability, all components easily accessible and replaceable from the front
- Stainless steel basket hanger lifts off for easy cleaning
- Food particles fall below burner tubes into cold zone to prolong shortening life
- Large 1¹/₄" ball-type full port drain valve prevents clogging









-31" (79 cm)

1/2" NPT Inlet Pipe Required -

(46 cm) Cook Area

> 16.5" (42 cm)

> > 9.75"

(25 cm)

**Front View** 

## **SPECIFICATIONS**

■ Model

■ Certification

■ Gas Input

■ Gas Pressure

■ Gas Connection

■ Electrical Requirements

■ Thermostat

■ Temperature Range

■ Hi-Limit

■ Safety Pilot

Burners

■ Frypot

Cabinet

■ Shortening Capacity

■ Cooking Capacity

■ Frying Area

■ Shipping Weight

■ Warranty

SLG100, Stainless steel frypot

ETL, cETL, ETL Sanitation

150,000, BTU/hr.

NG 3.5" WC, LP 10" WC

1/2" NPT

None

Snap action millivolt control

175°-375°F (79°-190°C)

Safety control turns off gas supply at

428°F (220°C)

100% gas shut off valve

Cast iron, atmospheric pre-mix

Stainless steel

Door, stainless steel

Backsplash, stainless steel

Basket Hanger, stainless steel

70-100 lbs

90 lbs of fries per hour

18" x 18" (46cm x 46cm)

200 lbs.

1 year parts and labor

Stainless steel frypot: 5 years

(pro-rated)

## **OPTIONS AND ACCESSORIES**

- Single or triple baskets
- Casters
- Drain Table
- Fryer Cover

# Top View 45.5" (116 cm) (21 cm) Side View 47.25" (120 cm)


## **STANDARD ACCESSORIES**


- 2 Twin nickel plated baskets
- Rack type basket support
- 6" Adjustable legs
- Drain pipe extension
- Flue extension/Diverter

## **DESIGN FEATURES**



Optimum access to cold zone





# Tapered Elliptical Shape

- 14% more surface area for heat transfer
- Food particles cannot accumulate on top of tubes

Specifications subject to change without notice.

Printed in the U.S.A.

Anetsberger Brothers reserves the right to replace a SilverLine product rather than replacing a fry pot.