



SC-GH

High Efficiency Gas Convection Steamer
on a Modular Cabinet Base



SC-10GH shown

OPTIONS AND ACCESSORIES

(AT ADDITIONAL CHARGE)

- ☐ 220 VAC, 1 phase, 60 hz
- ☐ Correctional package
- ☐ 120 minute timer
- ☐ One year extended warranty

CAPACITY

- Model SC-5GH is comprised of one 5 pan compartment
- Model SC-7GH is comprised of one 3 pan and one 4 pan compartment
- Model SC-10GH is comprised of two 5 pan compartments
- Model SC-16GH is comprised of two 8 pan compartments

Model	Pan Depth			
	1"	2.5"	4"	6"
SC-5GH	10	5	3	2
SC-7GH	14	7	4	2
SC-10GH	20	10	6	4
SC-16GH	32	16	8	6



Project _____

Item No. _____

Quantity _____

- ☐ Model SC-5GH (5 pan high efficiency gas convection steamer)
- ☐ Model SC-7GH (7 pan high efficiency gas convection steamer)
- ☐ Model SC-10GH (10 pan high efficiency gas convection steamer)
- ☐ Model SC-16GH (16 pan high efficiency gas convection steamer)

EXTERIOR CONSTRUCTION

- 304 satin finish stainless steel
- Welded stainless steel door with removable inner stainless steel liner
- Full perimeter door gasket
- Positive lock and seal mechanism with spring release on door
- Stainless steel control housing
- All stainless steel construction for generators and cabinet base

INTERIOR CONSTRUCTION

- One piece welded 316 stainless steel cooking chamber
- Coved corners
- Stainless steel pan supports
- Stainless steel drip trough integrally connected to drain

OPERATION

- Pressureless steam operation
- Automatic generator blowdown
- Separate controls for each compartment
- Full access removable left and right side panel
- Illuminated on/off/delime power switch
- Ready indicator light
- Cooking indicator light
- Electronic ignition with ignition light
- 60 minute electric timer with audible alarm to signal end of cook cycle
- Solid state generator controls with electronic ignition
- Steam flow to the cooking chamber is cut off when the door is opened during the cooking cycle and reactivated when the door is closed

STANDARD FEATURES

- Delime mode power switch
- Deliming ports on front of each generator
- Electromechanical controls
- Split water connections
- 24" wide cabinet base with hinged door and 6" (152 mm) legs for 5, 7 and 10 pan steamers
- 36" wide cabinet base with hinged doors and 6" (152 mm) legs for 16 pan steamers
- Redundant controls and generators for each compartment
- Thermostatically controlled drain for steam condensate
- Rear flanged feet
- 120 VAC, 1 phase, 60 hz
- One year parts and labor steamer warranty*
- Five year limited steamer door warranty*

* For all international markets, contact your local distributor.

SC-GH CONVECTION STEAMER

BLODGETT OVEN COMPANY

www.blodgett.com

44 Lakeside Avenue, Burlington, VT 05401 • Phone: (802) 658-6600 • Fax: (802) 864-0183

