BUNN®

12 Cup Automatic Coffee Brewer with 4 or 6 Warmers

ITEM#

PROJECT

DATE



Model CWTF 4/2 Twin (decanters sold separately) Dimensions: 19.1" H x 16.5" W x 19.8" D (49cm H x 41.9cm W x 50.3cm D)

Features

12 Cup Automatic Coffee Brewer

- Medium volume, twin brew head systems.
- Brews 15 gallons (56.8 litres) of perfect coffee per hour.
- Four or six individually controlled warming stations.
- All stainless steel construction.
- Includes hot water faucet.
- Pourover feature on both sides.
- SplashGard® funnel deflects hot liquids away from the hand.

For current specification sheets and other information, go to www.bunn.com.

Related Products

Easy Clear® EQ-17-TL Product No. : 30200.1000 Dimensions: 12^{7}_{16} " H x 2^{1}_{2} " W x 3" D 31.6 cm H x 6.35 cm W x 7.62 cm D

Easy Clear® ED-17-TL Product No. : 30201.1001 Dimensions: 8¹⁄₄" H x 2⁵⁄₁₆" Dia. 20.95 cm H x 5.87 cm Dia.



Paper Filter Pack Product No. : 20115.0000 Packed per case: 1,000 Dimensions: 4¹/₄" Base x 2³/₄" Sidewall 10.8 cm Base x 6.98 cm Sidewall

Easy Pour® black decanter Product No. : 06100.0101 Quantity: 1 (also packaged in quantities of 2, 3, 6, 12, & 24)



Easy Pour® orange decanter (for decaf) Product No. : 06101.0101 Quantity: 1 (also packaged in quantities of 2, 3, 6, 12, & 24) 1GPR SS Portable Server on an RWS1 Warmer 1GPR Product No. : 12487.0001* RWS1 Product No. : 12203.0010 *Also available with side handles or black decor.



Model Agency Listing CWTF 2/2 Twin (1) ustre (16) CWTF 4/2 Twin (1) ustre (16) Patents Apply 10/09 A1.9

Dimensions & Specifications


Model	Product #	Volts	Amps	Tank Heater Watts	Total Watts	Brewing Capacity	Cu. Ft.	Shipping Weight	Cord Attached
CWTF 2/2 Twin	23400.0001	120/240	27.7	2 @ 3000	6650	15 gal./hr.	6.4	56 lbs.	No
CWTF 4/2 Twin	23400.0011	120/240	28.5	2 @ 3000	6850	15 gal./hr.	6.4	56 lbs.	No

Brewing capacity: based upon incoming water temp of 60°F (140°F rise) per 1/2 gallon brew time of 4 minutes.

Models listed as 120/208V or 120/240V must be connected to 208V or 240V electrical service respectively. Please refer to the installation manual.

Electrical: Model requires 3-wires plus ground service rated 120/240V, single phase, 60 Hz.

Plumbing: 20-90 psi (138-621 kPa). Machine supplied with ³/₈" male flare fitting.



Bunn-O-Matic® Corporation - 1400 Stevenson Drive Springfield, Illinois 62703 • 800-637-8606 • 217-529-6601 • Fax 217-529-6644 • www.bunn.com

BUNN® practices continuous product research and improvement. We reserve the right to change specifications and product design without notice. Such revisions do not entitle the buyer to corresponding changes, improvements, additions or replacements for previously purchased equipment. All dimensions shown in inches 10/09 © Bunn-O-Matic Corporation