

High Volume Liquid Coffee Refrigerated Dispenser

ITEM#

PROJECT

DATE



Model LCR-3 HV

Dimensions: 40" H x 33" W x 23.6" D
(101.6 cm H x 83.8 cm W x 59.9 cm D)

Features

Liquid Coffee Refrigerated Dispenser

High volume Coffee-On-Demand dispenser meets the requirements of banquet halls, convention centers, stadiums and hotels

- Refrigerated product cabinet extends product flavor profile, adjustable to maintain 41° to 65°F in the product compartment.
- LCD screen for programming and user interface.
- Holds up to three 1-gallon BIB's.
- Delivers 6 oz. per second of hot coffee on demand, 30-145 gallons of coffee per hour (varies by voltage and incoming water temperature).
- 3-phase or single phase operation.
- In two flavor mode, the optional "Auto-Switching" function automatically switches from an empty BIB to a secondary BIB (left and middle pump only).
- Three dispense buttons allow operator to dispense three independent ratios.
- Each dispense button allows the option of up to 3 portion sizes via rotary selection switch.
- 18 gallon (82L) tank capacity.
- Manual hot water faucet.
- Sanitation listed by NSF Standard 18 and safety listed by UL Standard (UL 197).

For current specification sheets and other information, go to www.bunn.com.


Related Products

Easy Clear® EQHP-54
Product No. : 39000.0006

Easy Clear® EQHP-54L
Product No. : 39000.0003

Easy Clear® EDSS-11-T200F System
Product No. : 30370.1000

Easy Clear® EDSS-11-T200F Cartridge
Product No. : 30370.1001



Scholle BIB connector
Product No. : 35057.0000



LiquiBox QC/D II BIB connector
Product No. : 35055.0000

250ml Graduated Cylinder
Product No. : 34028.0000
For use in calibration of pumps.



BIB compartment view

Model

LCR-3, HV

Agency Listing



Dimensions & Specifications

Model	Product Number	Product Ratios	Connector Type	Cubic Feet	Shipping Weight	Cord Attached
LCR-3, HV	40800.0000	25:1-100:1	Scholle QC	38*	225 lbs.*	No
LCR-3, HV	40800.0001	25:1-100:1	Scholle 1910	38*	225 lbs.*	No
LCR-3, HV	40800.0002	25:1-100:1	Scholle QCD-II	38*	225 lbs.*	No

*unit is shipped strapped to pallet


Power Volts	Phase	Heater Watts	Total Amps	Capacity Cups/Hr**	Gal/Hr
120/208	1 Phase	7820	37.6	641	25.0
120/240	1 Phase	10400	43.2	853	33.3
120/208 Y	3 Phase	12000	32.8	961	37.6
120/240 Y	3 Phase	15000	37.6	1280	49.6

**Capacity measured with a 5 oz. cup and can be increased by preheating incoming water to 140°F maximum.

Electrical: Electrical: 4-wires plus ground service rated 120/208V, 3-phase 60Hz. Machine requires L1 to Neutral to be 120Vac.

Optional Configurations: 3-wires plus ground service rated 120/208 or 120/240V, 1-phase 60Hz.

Plumbing: 20-90 psi (138-621 kPa) from a 3/8" (10 mm) or larger supply line. Unit requires a 3 gpm line flow capacity. A shut-off valve should be installed in the line before the unit. Install a regulator in line when pressure is greater than 90 psi to reduce pressure to 50 psi. Supplied with 3/8" (10 mm) male flare fitting. Filtering recommended.



Bunn-O-Matic® Corporation - 1400 Stevenson Drive Springfield, Illinois 62703 • 800-637-8606 • 217-529-6601 • Fax 217-529-6644 • www.bunn.com

BUNN® practices continuous product research and improvement. We reserve the right to change specifications and product design without notice. Such revisions do not entitle the buyer to corresponding changes, improvements, additions or replacements for previously purchased equipment.

All dimensions shown in inches.

9/10 © Bunn-O-Matic Corporation