

## Dual Soft Heat® Brewer with Docking System

ITEM#

PROJECT

DATE



### Dual SH with SH Servers

*(servers sold separately)*

Dimensions: 35.8" H x 18" W x 20.5"D  
(91cm H x 45.7cm W x 52.1cm D)

### Features

#### Coffee brewers with portable servers

- Variable batch selector allows you to brew ½, 1, or 1½ gallon (1.9, 3.8 or 5.7 litre) batches.
- Patented server heat control automatically shuts off once target temperature is reached. Can be set to 175°–190°F (79.4–87.8°C).
- Electronic grinder interface instructs grinder on exact amount of coffee for selected brew batch size.
- Master on/off switch.
- Safety-Fresh® patented brew-through lid with vapor seal and spill prevention.
- Holds two SH servers (sold separately).
- Remote 1 or 2 server docking stations for additional satellite coffee serving. (sold separately)
- Brew capacity varies by model. See back for details.

For current specification sheets and other information, go to [www.bunn.com](http://www.bunn.com).

*International models may vary in appearance.*

### Related Products

Easy Clear® EQHP-25L  
Product No. : 39000.0002



Easy Clear® EQHP-25  
Product No. : 39000.0005

Single/Dual Filter Pack  
Product No. : 20138.0000



SH Server  
Product No. : 27850.0001



Two Position Drip Tray  
Product No.: 27150.0000



2SH Stand  
Product No. : 27875.0001  
(230 volt)



## Dimensions & Specifications

Model	Product #	Volts	Amps	Tank Heater Watts	Total Watts	Brewing Capacity	Shipping Weight	Cord Attached	Agency
Dual SH Brewer	27900.0006	230	26.9	2@3031	6200	17.3 gal./hr. (71.5 L/hr)	89 lbs. (40.4 kg)	No	CE
Dual SH Brewer	27900.0037	220	25.5	2@3031	5600	17.3 gal./hr. (71.5 L/hr)	92 lbs. (41.7 kg)	No	

**Note:** Soft Heat® Brewers and Servers are sold, boxed and shipped separately. All brewers have mechanical thermostats.

**Brewing capacity:** based upon incoming water temp of 60°F/15.5°C (140°F/60°C rise) per ½ gallon (1.89 L) brew time of 4 minutes.

Electrical: 230 volt model requires 2-wires plus ground service rated 220-240V, single phase, 50/60Hz.

220 volt model requires 2 wires plus ground service rated 220-240V, single phase, 60Hz.

Plumbing: 20-90 psi (138-621 kPa). Machine supplied with ¼" male fitting. Tank capacity: 8.4 gallons (31.8 L)

