

BrewWISE® Dual ThermoFresh® DBC Multi-Phase Brewer

ITEM#

PROJECT

DATE



Dual TF DBC Multi-Phase with 1.5 gallon TF Servers *(servers sold separately)*

Dimensions: 35.7" H x 21.8" W x 20.2" D
(90.7cm H x 55.4cm W x 51.3cm D)

Features

BrewWISE® Brewing System with ThermoFresh® Servers

- Brewer can be field converted to operate on either 3 phase or 1 phase.
- Stores individual coffee recipes so operator can easily brew many varieties.
- Coffee extraction controlled with pre-infusion and pulse brew, digital temperature control and large sprayhead; coffee strength controlled with variable by-pass.
- Operate any combination of BrewWISE® equipment error-free with wireless brewer-grinder interface through the Smart Funnel®.
- SplashGard® funnel and optional funnel locks help improve safety.
- Master on/off switch.
- ThermoFresh® servers are vacuum insulated to keep coffee hot and fresh for hours. (sold separately)
- Create coffee recipe cards with custom recipes, ad cards with messages that display on the brewer LCD, and dedicated funnels for special coffees with the BrewWISE Recipe Writer using your PC (U.S. and English Windows® compatible).
- Brew capacity varies. See back for details.

For current specification sheets and other information, go to www.bunn.com.

Related Products

Easy Clear® EQHP-25L
Product No.: 39000.0002



Easy Clear® EQHP-25
Product No.: 39000.0005

Single/Dual Filter Pack
Product No.: 20138.0000



BrewWISE® Recipe Writer (BRW)
Product No.: 34444.0001



Recipe Card
Product No.: 34447.0000

- Program a recipe to be used on brewer or grinder.



Ad Card
Product No.: 34448.0000

- Program a message to appear on the brewer's display.



Multi-Hopper Grinder (MHGA)
Product No.: 35600.0003
(230 volt black finish)



TF Servers
Product No.: 39550.0001
• 1.5 gallon, Mechanical Gauge, Black
Product No.: 39550.0000
• 1.5 gallon, Mechanical Gauge, Stainless Steel



TF Digital Servers
Product No.: 39550.0051
• 1.5 gallon, Digital Gauge, Black
Product No.: 39550.0050
• 1.5 gallon, Digital Gauge, Stainless Steel



Dimensions & Specifications

Model	Product #	Shipping Weight	Cord Attached	Agency
Dual TF DBC Multi-Phase	34600.0020	92.5 lbs. (42 kg)	No	CE P _{CE}
Dual TF DBC Multi-Phase*	34600.0025	92.5 lbs. (42 kg)	No	CE P _{CE}

*(black decor)

Phase	Volts	Amps	Tank Heater Watts	Total Watts	Brewing Capacity
3 (w/neutral)	230/400	16 (per phase)	9093	11,125	26 gal/hr (98 L/hr.)
1	230	27.2	2@3030	6265	17.3 gal/hr (65.5 L/hr.)

Brewing capacity: based upon incoming water temp of 60°F (15.5°C), 140°F rise (60°C) per 1/2 gallon brew time of 4 minutes.
Equipped with funnel locks.

Electrical: Brewer is configured for 3-phase (with neutral) use. By moving one wire in brewer's terminal block, the same unit can be configured for 1-phase (230 volt) operation.

3-Phase - Phase to phase = 400V (will work on any voltage rated 380-415). Phase to neutral = 230V.

4 wire plus ground, 50/60 Hz, 3 active heaters.

1-Phase - Voltage = 230, 2 wire plus ground, 50/60Hz, 2 active heaters.

Plumbing: 20-90 psi (138-621 kPa). Machine supplied with 1/4" male fitting. Tank capacity: 10.6 gallons (40.1 L)

