

CDBCF Automatic Coffee Brewer with Pourover



CDBCFP

(2 top warmers)

(decanters sold separately)

Dimensions: 20.9" H x 8.5" W x 17.8" D

(53.1cm H x 21.6cm W x 45.2cm D)

Features

Automatic CDBCF Coffee Brewer with Pourover

- Large 200 oz. (5.9 litres) tank provides back-to-back brewing capacity.
- Adjusts automatically to varying water pressure.
- Pot level, cold brew lock-out and tank temperature set easily from advanced touch pad on front of machine.
- Electronic diagnostics and built in tank drain make service easier.
- Ensures coffee brew quality with cold brew lock out capability.
- SplashGard® funnel deflects hot liquids away from the hand.
- Coffee extraction controlled with pre-infusion or pulse brew and digital temperature control.
- Stainless steel funnel.
- Pourover feature.
- Brew capacity varies by model. See back for details.

For current specification sheets and other information, go to www.bunn.com.

International model may vary in appearance.

Related Products

Easy Clear® EQ-17-TL

Product No. : 30200.1000



Paper Filter Pack

Product No. : 20115.0000

Packed per case: 1,000



Easy Clear® ED-17-TL

Product No. : 30201.1001

Easy Pour® black decanter

Product No. : 06100.0101

Quantity: 1 (also packaged in quantities of 2, 3, 6, 12, & 24)



Easy Pour® orange decanter (for decaf)

Product No. : 06101.0101

Quantity: 1 (also packaged in quantities of 2, 3, 6, 12, & 24)



Dimensions & Specifications

| Model | Product # | Volts | Amps | Tank Heater Watts | Total Watts | Brewing Capacity | Shipping Weight | Cord Attached | Agency |
|-------------------|------------|-------|------|-------------------|-------------|----------------------------|----------------------|---------------|--------|
| CDBCFA (2 top) | 28800.0316 | 230 | 8.8 | 1850 | 2030 | 4.5 gal./hr. (17 L/hr.) | 32 lbs. (14.5 kg) | Yes | CE |
| Power cord | 27728.0001 | | | | | | | | |

Brewing capacity: based upon incoming water temp of 60°F /15°C (140°F/60°C rise) per 1/2 gallon (1.9 L) brew time of 4 minutes.

Electrical: Model requires 2-wires plus ground service rated 220-240V, single phase, 50/60 Hz.

Plumbing: 20-90 psi (138-621 kPa). Machines supplied with 1/4" male flare fitting.

