

## Features

### Coffee brewers with portable servers

- Brews 11.4 to 12.3 gallons of perfect coffee per hour.
- Versatile single-headed brewer – brews ½, 1, or 1½ gallon batches.
- Coffee stays fresh in super-insulated servers which need no electricity, warmers, or burners.
- Brew Smart® variable bypass ensures perfect coffee regardless of batch size.
- Safety-Fresh® patented brew-through lid with vapor seal and spill prevention.
- Perfect for quick turn uses where high quality coffee is continuously refreshed.
- International electrical configurations available.



*Model Single TF with  
1.5 gallon TF Server  
(server sold separately)*

## Related Products

For available variations to some BUNN products, please contact your BUNN sales representative.

BUNN recommends the use of our EasyClear® water filters and BUNN paper filters to assure perfect taste. Our water filters remove sediment, bad taste and odor, while reducing lime. BUNN paper filters are naturally biodegradable. Made from 100% pure virgin fiber, they assure proper porosity, flow rate, and paper structure for absolute brewing consistency.

### EasyClear® CP-110 Water Filter with Bracket & Shutoff valves

Product No. : 30044.1000

Dimensions: 13½ H" x 8" W x 5¼ D



### Single/Dual Filter Pack

Product No. : 20138.0000

Packed per case: 1,000

Dimensions:

5¼" Base x 4¼" Sidewall



### ThermoFresh 2000 Server

Product No.: 25800.0001

Capacity: 1½ Gallons



ITEM#

PROJECT

DATE

## Models

### Single TF

## BUNN®

### Corporate Offices

1400 Stevenson Drive  
Springfield, Illinois 62703

### Phone

800-637-8606

217-529-6601

### Fax

217-529-6644

### Technical Services

800-286-6070

### Internet

<http://www.bunnomatic.com>

### Western Regional Office

16431 Carmenita Road,  
Cerritos, California 90701

### Phone

562-926-0764

### Fax

562-926-0858

### Canadian Office

280 Industrial Parkway South  
Aurora, Ontario, L4G 3T9

### Phone

905-841-2866

### Fax

905-841-2775

Patents  
Apply

BUNN® practices continuous product research and improvement. We reserve the right to change specifications and product design without notice. Such revisions do not entitle the buyer to corresponding changes, improvements, additions or replacements for previously purchased equipment.

## Dimensions & Specifications

Model	Product #	Volts	Amps	Tank Heater Watts	Total Watts	Brewing Capacity	Cu. Ft.	Shipping Weight
Single TF Brewer	23050.0030	120/208	19.46	3700	3950	11.4 gal./hr.	9.1	57 lbs. (25.9 kg)
Single TF Brewer	23050.0031	120/240	18.33	4000	4250	12.3 gal./hr.	9.1	57 lbs. (25.9 kg)

Note: ThermoFresh brewers and servers are boxed and shipped separately. Both models listed feature variable bypass, stainless steel funnels, hot water faucet, and 3 batch settings.

Electrical: Units require 3-wire, grounded service rated 120/208V or 120/240V, single phase, 60 Hz.

Plumbing: 20-90 psi (69-621 kPa).

