

Features

12 Cup Automatic Coffee Brewer

- Brews 3.9 to 6.8 gallons of perfect coffee per hour.
- Model is space-saving 7.5" wide.
- All stainless steel construction.
- Available with hot water faucet.
- Pourover feature available.
- Three built-in separately controlled warmers.
- Plastic funnel available.
- SplashGard™ funnel deflects hot liquids away from the hand.
- UL listed. NSF approved.



*Model STFP
(decanters not included)*

ITEM#

PROJECT

DATE

Model

*ST
STF
STFP*

Related Products

For available variations to some BUNN products, please contact your BUNN sales representative.

BUNN recommends the use of our Easy Clear® Water Quality Systems and BUNN paper filters to assure perfect taste.

Easy Clear® EQ-17-TL

Product No. : 30200.1000

Dimensions:

12⁷/₁₆" H x 2¹/₂" W x 3" D



Easy Clear® ED-17-TL

Product No. : 30201.1001

Dimensions: 8¹/₄" H x 2⁵/₁₆" Dia.

Paper Filter Pack

Product No. : 20115.0000

Packed per case: 1,000

Dimensions: 4¹/₄" Base x 2³/₄" Sidewall



Easy Pour® black decanter

Product No. : 06100.0101

Quantity: 1 (also packaged in quantities of 2, 3, 6, 12, & 24)



1GPR SS Portable Server on an RWS1 Warmer

1GPR Product No. : 12487.0001*

RWS1 Product No. : 12203.0010

*Also available with side handles or black decor.



BUNN®

Corporate Offices
1400 Stevenson Drive
Springfield, Illinois 62703

Phone

800-637-8606

217-529-6601

Fax

217-529-6644

Technical Services

800-286-6070

Internet

<http://www.bunnomatic.com>

Western Regional Office

16431 Carmenita Road,
Cerritos, California 90701

Phone

562-926-0764

Fax

562-926-0858

Canadian Office

280 Industrial Parkway South
Aurora, Ontario, L4G 3T9

Phone

905-841-2866

Fax

905-841-2775

Patents

Apply

Dimensions & Specifications

Model	Product #	Volts	Amps	Tank Heater Watts	Total Watts	Brewing Capacity	Cu. Ft.	Shipping Weight	Cord Attached
ST-15	02700.0020	120	15	1425	1800	3.9 gal./hr.	3.8	28 lbs. (12.7 kg)	Yes
ST-20	02700.0021	120	18	1800	2200	5.5 gal./hr.	3.8	28 lbs. (12.7 kg)	No
ST-35	02700.0022	120/240	16.3	3500	3900	6.8 gal./hr.	3.8	28 lbs. (12.7 kg)	No
STF-15	02700.0040	120	15	1475	1800	3.9 gal./hr.	3.8	30 lbs. (13.6 kg)	Yes
STF-20	02700.0041	120	18	1800	2200	5.5 gal./hr.	3.8	30 lbs. (13.6 kg)	No
STF-35	02700.0042	120/240	16.3	3500	3900	6.8 gal./hr.	3.8	30 lbs. (13.6 kg)	No
STFP-15	02700.0043	120	15	1425	1800	3.9 gal./hr.	3.8	29 lbs. (13.2 kg)	Yes
STFP-20	02700.0044	120	18	1800	2200	5.5 gal./hr.	3.8	29 lbs. (13.2 kg)	No
STFP-35	02700.0045	120/240	16.3	3500	3900	6.8 gal./hr.	3.8	29 lbs. (13.2 kg)	No

Note: F in model name designates that this model has a faucet. P in model name designates plastic funnel; all other models come equipped with a stainless steel funnel.

Electrical: Model 15 requires 2-wires plus ground service rated 120V, single phase, 60 Hz.
 Model 20 requires 2-wires plus ground service rated 120V, single phase, 60 Hz.
 Model 35 requires 3-wires plus ground service rated 120/240V, single phase, 60 Hz.

Plumbing: 20-90 psi (138-621 kPa). Machine supplied with ¼" male flare fitting.

