


Titan™ Dual and Single Coffee Brewers



Titan Dual Brewer

High volume brewing solution featuring Digital Brewer Control, precise extraction control and portable servers

- Coffee extraction controlled with pre-infusion and pulse brew, digital temperature control, and large sprayhead; variable by-pass controls coffee strength.
- BrewMETER® allows automatic programming of pulse routine. 
- Funnel has 28 ounce (.8 litre) capacity and paper filter retainers to eliminate fold-over.
- Left or right faucet for hot water.
- Use BUNN paper filter – Product No. 20111.0000.






Titan TF Server

TITAN TF SERVER

- Insulated server keeps coffee hot for hours.
- Contemporary styling and wrap program for maximum merchandising.
- Large cup clearance allows for dispensing into cups, decanters and thermal carafes.
- Integrated sight gauge assembly allows for easy cleaning.



Titan Single Brewer




Model	Product #	Volts	Amps	Watts	Brewing Capacity	Dimension	Weight	Cord Attached	Agencies
Titan Dual	39200.0000	120/208 <i>(3 phase)</i>	33.4	12000	34.3 gal. (129.8 L)	40"H x 35.6"W x 21.7"D (101.7cm H x 90.5cm W x 55.2cm D)	148 lbs. (67.1 kg)	No	
		120/208 <i>(1 phase)</i>	40.1	8200	22.9 gal. (86.7 L)				
Titan Single	39300.0000	120/208 <i>(3 phase)</i>	33.4	12000	22.5 gal. (85.2 L)	40.02" H x 21.3"W x 21.74" D (101.7cm H x 54.1cm W x 55.2cm D)	107 lbs. (48.5 kg)		
		120/208 <i>(1 phase)</i>	40.1	8200	17 gal. (64.4 L)				
Titan TF Server	39400.0001					23.7"H x 13.7"W x 17.1"D (60.2cm H x 34.8cm W x 43.4cm D)	17.5 lbs. (7.9 kg)		

BrewWISE® ThermoFresh® Brewers



BrewWISE Dual TF

The TF brewers use Digital Brewer Control and feature vacuum-insulated ThermoFresh servers that hold beverages at optimum flavor profile for hours without requiring the energy consumption of traditional warming plates





- Stores individual coffee recipes.
- Large sprayhead and BrewWISE intelligence for simplified programming. 
- Variable by-pass controls coffee strength.
- Simplify installation and calibration by creating coffee recipe cards and dedicated funnels with the Recipe Writer using your PC (U.S. and English MS Windows® compatible). 
- Equipped with tank drain.
- Use BUNN paper filter – Product No. 20138.0000.
- Compatible with BUNNlink®. 



BrewWISE
Recipe Writer



BrewWISE
Single TF

Model	Product #	Volts	Amps	Watts	Brewing Capacity	Funnel Locks	Finish	Dimension	Weight	Cord Attached	Agencies	
Single TF DBC	34800.0000	120/240	16.6	4000	11.4 gal. (43.2 L)	Yes	SST	35.7" H x 12.1"W x 19.2" D (90.7cm H x 30.7cm W x 48.8cm D)	59 lbs. (26.8 kg)	No	 	
	34800.0002	120/208	19.2			No						
	34800.0003	120/208	19.2			Yes						
	34800.0004	120/240	16.6			No						
	34800.0001					Yes	Black					
	34800.0008	120	18.1	2200	6.5 gal. (24.6 L)		SST					
	34800.0017	120				Black						
Dual TF DBC	34600.0000	120/240	27.5	6600	18.9 gal. (71.5 L)	No	Black	35.7"H x 21.8"W x 20.2"D (91.7cm H x 55.4cm W x 51.3cm D)	92.5 lbs. (42 kg)	No	 	
	34600.0001						SST					
	34600.0002						Black					
	34600.0003						SST					
	34600.0004	120/208	27.4	5700	16.3 gal. (61.7 L)	Yes	Black					
	34600.0005		27.4				SST					
	34600.0006		27.4				Black					
	34600.0007		27.4				SST					
Recipe Writer	34444.0000	120	1				Black	2.2" H x 6.4"W x 9.5" D (5.6cm H x 16.2cm W x 21.4cm D)	6.1 lbs. (2.8 kg)			
Recipe Card	34447.0000								1.2 lbs.			
Ad Card	34448.0000								1.2 lbs.			

Digital ThermoFresh® Servers and Stand



1.5 Gal TF Server

ThermoFresh servers hold beverages at optimum flavor profile for hours without requiring the energy consumption of traditional warming plates

- Four-hour digital count-up timer.
- Volume indicator display.
- Vacuum insulated.
- Unique lid design features a pour spout for easy emptying and cleaning.
- Contemporary styling and wrap program for maximum merchandising.
- Digital sight gauge has a count-up timer that begins to count-up in one minute increments to specifically display how long the brewed beverage has been stored. Operates on four AAA batteries with an average 1-year lifespan. Display shows low battery symbol.
- Translucent faucet guard provides increased visibility while dispensing.
- Brew-through lid.
- Soft grip handle for easy transportation.

TF SERVER WITH BASE

- Built-in drip tray is easily removed for cleaning or providing extra clearance for large vessels.
- Large cup clearance.
- Ideal for use with Single or Dual DBC Brewers.



Baseless 1.5 Gal
TF Server

TF BASELESS SERVER

- 7.05" (17.9 cm) cup clearance.
- Ideal for use with the Infusion Coffee Brewer (ICB)
- Use with the TF Server Stand for easy dispensing. Product No. 39795.0000



TF Server Stand



Digital Sight Gauge
with Count-up Timer

Model	Product #	Holding Capacity	Finish	Dimension	Weight	Cord Attached	Agencies
TF Server	42700.0000	1 gal (3.8 L)	SST	20.6" H x 9.3" W x 13" D (52.3cm H x 23.6cm W x 33cm D)	15 lbs. (6.8 kg)	No	NSF.
	42700.0001		Black				
	42750.0000	1.5 gal (5.7 L)	SST	22.7" H x 9.3" W x 13" D (57.7cm H x 23.6cm W x 33cm D)	16 lbs. (7.3 kg)		
	42750.0001		Black				
Baseless TF Server	42700.0050	1 gal (3.8 L)	SST	12.6" H x 9.1" W x 12.7" D (32cm H x 23.1cm W x 32.3cm D)	11 lbs. (4.9 kg)	No	NSF.
	42700.0051		Black				
	42750.0050	1.5 gal (5.7 L)	SST	14.7" H x 9.1" W x 12.7" D (37.3cm H x 23.1cm W x 32.3cm D)	12 lbs. (5.4 kg)		
	42750.0051		Black				
TF Server Stand	39795.0000		Black	8.7" H x 9.4" W x 12.9" D (22.1cm H x 23.9cm W x 32.8cm D)	4.2 lbs. (1.9 kg)		

ThermoFresh® Servers and Stand



1.5 Gal TF Server

ThermoFresh servers hold beverages at optimum flavor profile for hours without requiring the energy consumption of traditional warming plates

- Vacuum insulated.
- Easily transport coffee to remote locations.
- Fast flow faucet.
- Brew-through lid.

TF SERVER WITH BASE

- Built-in drip tray is easily removed for cleaning or providing extra clearance for large vessels.
- Large cup clearance.
- Ideal for use with Single or Dual TF DBC Brewers.

TF Servers	For Use With	Page #
with base - digital or mechanical gauge	Single TF DBC	26
	Dual TF DBC	
	ICB Tall, ICB Twin Tall	18
	ITCB (tall)	51
	ITCB-DV HV, ITCB-Twin HV	52
baseless - digital or mechanical gauge	ICB	17
	ICB-Twin	

TF BASELESS SERVER


- Use with the TF Server Stand for easy dispensing. Product No. 39795.0003
- Ideal for use with the Infusion Coffee Brewer (ICB).



Baseless 1 Gal TF Server



TF Server Stand




Model	Product #	Holding Capacity	Finish	Dimension	Weight	Cord Attached	Agencies
TF Server	39500.0000	1 Gallon (3.8 L)	SST	20.8" H x 9.3" W x 13" D (52.8cm H x 23.6cm W x 33cm D)	13 lbs. (5.9 kg)	No	
	39500.0001		Black				
	39550.0000	1.5 Gallon (5.7 L)	SST	22.9" H x 9.3" W x 13" D (58.2cm H x 23.6cm W x 33cm D)	14 lbs. (6.4 kg)		
	39550.0001		Black				
Baseless TF Server	39500.0004	1 Gallon (3.8 L)	SST	12.8" H x 9.1" W x 13.1" D (32.5cm H x 23.1cm W x 33.3cm D)	13 lbs. (5.9 kg)		
	39500.0005		Black				
	39550.0004	1.5 Gallon (5.7 L)	SST	14.9" H x 9.1" W x 13.1" D (37.8cm H x 23.1cm W x 33.3cm D)	14 lbs. (6.4 kg)		
	39550.0005		Black				
TF Server Stand	39795.0003		Black	8.7" H x 9.4" W x 12.9" D (22.1cm H x 23.9cm W x 32.8cm D)	4.2 lbs. (1.9 kg)		

BrewWISE® Soft Heat® DBC® Brewers







BrewWISE Dual SH DBC

Soft Heat technology automatically manages heat in the server docking system to ensure optimum flavor profile for hours

- Brews ½, 1, or 1 ½ (1.9, 3.8 or 5.7 litre) gallon batches.
- Stores individual coffee recipes.
- Large sprayhead and BrewWISE intelligence for simplified programming. 
- Variable by-pass controls coffee strength.
- Dual holds two 1 ½ gallon (5.7 litre) SH servers. Single holds one server.
- Simplify installation and calibration by creating coffee recipe cards and dedicated funnels with the Recipe Writer using your PC (U.S. and English MS Windows® compatible). 
- Equipped with tank drain.
- Use BUNN paper filter – Product No. 20138.0000.
- Compatible with BUNNlink®. 



BrewWISE Single SH DBC

Model	Product #	Volts	Amps	Watts	Faucet Location	Brewing Capacity	Finish	Dimension	Weight	Cord Attached	Agencies
Single SH DBC	33600.0000	120/240	17.5	4100	Upper	11.4 gal. (43.2 L)	Stainless	35.8"H x 9.3"W x 23.1"D (90.9cm H x 23.6cm W x 58.7cm D)	59 lbs. (26.8 kg)	No	 
	33600.0001 (funnel lock)						Black				
	33600.0013										
Dual SH DBC	33500.0000	120/240	29.1	6800	Upper	18.9 gal. (71.5 L)	Stainless	35.8"H x 18"W x 21.2"D (90.9cm H x 45.7cm W x 53.8cm D)	90 lbs. (40.8 kg)	No	 
	33500.0004						Black		89 lbs. (40.4 kg)		
	33500.0006				Lower		Stainless		90 lbs. (40.8 kg)		

Soft Heat® Brewers





Dual SH

Soft Heat technology automatically manages heat in the server docking system to ensure optimum flavor profile for hours

- Variable batch selector knob allows ½, 1 or 1½ gallon (1.9, 3.8 or 5.7 litre) batches.
- Electronic grinder interface instructs grinder on exact amount of coffee for selected brew batch size.
- Dual holds two 1½ gallon (5.7 litre) SH servers. Single holds one server.
- Soft Heat® server heat control automatically shuts off once target temperature is reached. Can be set to 175°-190°F (79.4° - 87.8°C).
- Remote 1 or 2 server docking stations (sold separately).
- Equipped with tank drain.
- Use BUNN paper filter – Product No. 20138.0000.



Single SH

Model	Product #	Finish	Volts	Amps	Watts	Capacity	Dimension	Weight	Cord Attached	Agencies
Single SH	27800.0001	Stainless	120/208	18.3	3800	10.6 gal. (40.1 L)	35.8"H x 9.3"W x 20.2"D (90.9cm H x 23.6cm W x 50.8cm D)	61 lbs. (27.7 kg)	No	 
	27800.0002		120/240	17.9	4300	11.4 gal. (43.2 L)		59 lbs. (26.8 kg)		
	27800.0009		120	17.5	2100	5.1 gal. (19.3 L)		57 lbs. (25.9 kg)		
Dual SH	27900.0001	Stainless	120/208	28.3	5900	16.3 gal. (61.7 L)	35.8"H x 18"W x 20.5"D (91cm H x 45.7cm W x 52.1cm D)	90 lbs. (40.9 kg)		
	27900.0002		120/240		6800	18.9 gal. (71.5 L)		89 lbs. (40.4 kg)		
	27900.0020	Black	120/208		5900			90 lbs. (40.9 kg)		

Soft Heat® Servers and Stands



1 SH Server
and Docking Station

Soft Heat technology automatically manages heat in the server docking system to ensure optimum flavor profile for hours

SOFT HEAT® SERVER

- Soft Heat® servers supply controlled heat to coffee.
- LED power indicator.
- Safety-Fresh® brew-through lid with vapor seal and spill prevention.



	For Use With	Page #
Soft Heat Server	Single SH DBC	29
	Dual SH DBC	
	Single SH	30
	Dual SH	



2SH Docking Station

SOFT HEAT DOCKING STATION

- Remote one and two server docking stations.
- Instant power contact with servers.

Model	Product #	Volts	Amps	Watts	Capacity	Setting	Legs	Finish	Dimension	Weight	Cord Attached	Agencies
1SH Stand	27825.0000	120	0.75	90	1 SH Server		4"	Stainless	28.2"H x 10"W x 14"D (71.6cm H x 25.4cm W x 35.6cm D)	13 lbs. (5.9 kg)	Yes	 
	27825.0004						6"	Black				
	27825.0003						4"	Stainless				
2SH Stand	27875.0000	1.5	180	2 SH Servers	Black							
27875.0003												
SH Server	27850.0001				1 1/2 Gal			Stainless	16.6"H x 8.5"W x 14" D (42.2cm H x 21.6cm W x 35.6cm D)	17 lbs. (7.8 kg)	No	
	27850.0004							Black		18 lbs. (8.2 kg)		
	27850.0006				45 Min.			Stainless		17 lbs. (7.8 kg)		
	27850.0008				60 Min.			Black				
	27850.0009				Adjustable Timer			Stainless				
	27850.0016				240 Min.							
	27850.0022				120 Min.			Black				

BrewWISE® GPR DBC® Brewers



Dual



Single

Brewers that utilize Digital Brewer Control to manage the brewing process from start to finish and feature portable server solutions



- Brews 12.5 gallons (47.3 litres) per hour.
- Brews ½, 1 or 1½ gallon (1.9, 3.8 or 5.7 liter) batches.
- Stores individual coffee recipes so operator can easily brew many varieties.
- Coffee extraction controlled with pre-infusion and pulse-Brew, digital temperature control, and large sprayhead; coffee strength controlled with variable by-pass.*
- Operate any combination of BrewWISE® equipment error-free with wireless brewer-grinder interface through the Smart Funnel®.*
- Create coffee recipe cards with custom recipes, ad cards with messages that display on the brewer LCD, and dedicated funnels for special coffees with the BrewWISE Recipe Writer using your PC (Windows® compatible).*
- Dual voltage brewer can be connected to 120V, 120/208V or 120/240V electrical.
- Troubleshoot all switches and electrical components from the front panel with advanced diagnostic service tools.
- Programmable freshness indication.
- Message display alerts when freshness timer expires and when warmers will automatically shut off.
- Programmable warmer control.
- Energy Saver Mode.*
- BUNN warranty includes 3 years parts and labor on electronic control boards and 2 years parts and 1 year labor on all other components.

DUAL GPR DBC

- Brews 18.9 gallons (71.5 liters) per hour.
- Brews ½, 1, or 1½ gallon (1.9, 3.8 or 5.7 liter) batches.




* For detailed descriptions of BUNN terms, please refer to pages 1-2.

Model	Product #	Volts	Amps	Watts	Brewing Capacity	Finish	Dimension	Weight	Cord Attached	Agencies
Single GPR DBC	36100.0016	120	15	1800	4.7 gal. (17.8 L)	Stainless	29.6 H x 9.2" W x 20" D (75.2cm H x 23.4cm W x 50.8cm D)	67 lbs. (30.4 kg)	Yes	 
		120/208	16.8	3400	9.5 gal. (36 L)					
		120/240	19.2	4500	12.5 gal. (47.3 L)					
Dual GPR DBC	35900.0010	120/208-240	25 - 29	5200 - 6800	14.8-18.9 gal. (43.2 L)		29.3 H x 18" W x 20" D (74.4cm H x 45.7cm W x 50.8cm D)	90 lbs. (40.8 kg)	No	

Single® and Dual® Brewers





Dual

- Brews ½, 1 or 1½ gallon (1.9, 3.8 and 5.7 litre) batches.
- Adjustable bypass ensures perfect coffee regardless of batch size.
- Electronic timer ensures fast set up and accurate brew levels.
- Electronic grinder interface instructs G9T HD grinder on exact amount of coffee for selected brew batch size.
- 1.5 GPR portable server (included) has a Safety-Fresh® brew-through lid with vapor seal and spill protection. 
- Equipped with tank drain.
- Use BUNN paper filter – Product No. 20138.0000.

NOTE: Catalog icon legend can be found on page 1.



Single

Model	Product #	Volts	Amps	Watts	Brewing Capacity	Batch Settings	Funnel Type	Finish	Dimension	Weight	Cord Attached	Agencies
Single	23050.0006	120	17.5	2100	5.1 gal. (19.3 L)	One	Plastic	Stainless	29.3"H x 9.25"W x 19"D (74.4cm H x 54.9cm W x 48.3cm D)	57 lbs. (25.9 kg)	No	 
	23050.0007			2100		Three	Stainless			58 lbs. (26.3 kg)		
	23050.0010	120/208	18.3	3800	10.6 gal. (40.1 L)					59 lbs. (26.8 kg)		
	23050.0011	120/240	17.9	4300	11.4 gal. (43.2 L)							
Dual	20900.0008	120/208	28.8	5990	16.3 gal. (67.7 L)	One	Plastic		29.3"H x 18"W x 19.3"D (74.4cm H x 45.7cm W x 49cm D)	92 lbs. (41.8 kg)		
	20900.0010					Three	Stainless			94 lbs. (42.7 kg)		
	20900.0011	120/240	28.7	6890	18.9 gal. (71.5 L)					95 lbs. (43.1 kg)		

I Gallon Automatic Brewers ⚡



Single AXIOM





Single CWTF

SINGLE AXIOM®

- Brews 4.5 to 9.0 gallons (17.0 to 34.1 litres) of perfect coffee per hour.
- 1/2 gallon and 1 gallon (1.9 and 3.8 litre) batches brewed into 1.5 GPR portable server *(included)*.
- Large 200oz. (5.9 litre) tank.
- Adjusts automatically to varying water pressure.
- For high lime areas, BrewLOGIC® technology calculates flow rate and adjusts brew time to maintain consistent pot levels. 🔍
- BrewWIZARD® technology simplifies brewer programming. 🔍
- Gourmet funnel allows use of heavier throw weights of coffee.

SINGLE CWTF

- Brew half gallon and 1 gallon (1.9 and 3.8 litre) batches into included 1.5 GPR portable server.
- Gourmet funnel models allows use of heavier throw weights of coffee.
- 1.5 GPR portable server *(included)* has a Safety-Fresh® brew-through lid with vapor seal and spill protection.
- Half gallon (1.9 litre) pourover backup.
- Gourmet funnel requires BUNN paper filter 20100.0000.

Model	Product #	Finish	Volts	Amps	Watts	Brewing Capacity	Funnel Type	Dimension	Weight	Cord Attached	Agencies
Single AXIOM-15	38700.0043	Stainless	120	13.8	1600	4.5 gal. (17 L)	Gourmet Stainless	26.1"H x 8.5"W x 18.9"D (66.3cm H x 21.6cm W x 48cm D)	30 lbs. (13.6 kg)	Yes	 
Single AXIOM-35	38700.0045		120/208-240	15.8	3650	7.5/9.0 gal. (28.4/34.1 L)				No	
Single CWTF15	35000.0004		120	13.8	1650	3.8 gal. (14.4 L)			46.5 lbs. (21 kg)	Yes	
Single CWTF35	35000.0006		120/208-240	15.8	3650	7.5/9.0 gal. (28.4/34.1 L)				No	

Portable Servers and Warmers



1.5 GPR
Portable Server

PORTABLE SERVER

- 1 or 1 ½ gallon (3.8, 5.7 litre) capacities.
- Easily transport portable servers for remote service.
- Safety-Fresh® brew-through lid with vapor seal and spill protection GPR servers.





RWS1
Warmer

WARMER

- Available with plastic, satin nickel or stainless steel legs.
- Legs are adjustable on RWS1.

	For Use With	Page #
GPR Server	Single GPR DBC	32
	Dual GPR DBC	
	Single CWTF	34
	Single AXIOM	
	Single	33
	Dual	

Model	Product #	Dimension	Weight	Finishes	Volts	Amps	Watts	Capacity	Cord Attached	Agencies				
1 GPR <i>(bail handle)</i>	12487.0001	14"H x 8.5"W x 12.7"D (35.6cm H x 21.6cm W x 32.2cm D)	8.5 lbs. (3.9 kg)	Stainless				1 gal (3.8 L)						
1 GPR <i>(side handle)</i>	12487.0003													
1 GPR-FF <i>(bail handle, fast flow faucet)</i>	12487.0005													
1.5GPR-FF <i>(top handle, fast flow faucet)</i>	20950.0004	18.1"H x 8.5"W x 12.7"D (46cm H x 21.6cm W x 32.2cm D)	10 lbs. (4.5 kg)					1 1/2 gal (5.7 L)						
RVWS1 <i>(plastic legs)</i>	12203.0010	7.5" H x 8.25"W x 9.3" D (19.1cm H x 21cm W x 23.6cm D)	7 lbs. (3.2 kg)		120	0.8	100				1 or 1.5 GPR	Yes		
RWS1 <i>(satin nickel legs)</i>	12203.0014		9 lbs. (4.1kg)											