

Liquid Coffee Refrigerated Dispenser - High Volume



LCR-3 HV

High volume Coffee-On-Demand dispenser meets the requirements of banquets, convention centers, and hotels



- Refrigerated product cabinet extends product flavor profile, adjustable to maintain 41° to 65°F (5° to 18°C) in the product compartment.
- Digital Brewer Control for programming and user interface.
- Holds up to three 1-gallon (3.79 L) BIBs.
- Delivers 6 oz.. (177 mL) per second of hot coffee on demand, 30-145 gallons (113-548.9 L) of coffee per hour (*varies by voltage and incoming water temperature*).
- 3-phase or single phase operation.
- In two flavor mode, the optional "Auto-Switching" function automatically switches from an empty BIB to a secondary BIB (*left and middle pump only*).
- Three buttons allow operator to dispense three independent ratios.
- Each dispense button allows the option of up to 3 portion sizes via rotary selection switch.
- 18 gallon (82L) tank capacity.
- Manual hot water faucet.



BIB compartment view

POWER Volts	Phase	Heater Watts	Total Amps	CAPACITY Cups/Hr** Gal.	
120/208	1 Phase	7820	37.6	641	25.0
120/240	1 Phase	10400	43.2	853	33.3
120/208 Y	3 Phase	12000	32.8	961	37.6
120/240 Y	3 Phase	15000	37.6	1280	49.6

**Capacity measured with a 5 oz.. cup and can be increased by preheating incoming water to 140°F maximum.

Model	Product #	Product Ratios	Dispense Rate/Sec.	Connector Type	Dimension	Weight	Volts/Amps/Watts/Capacity	Cord Attached	Agencies
LCR-3 HV	40800.0000	25:1 - 100:1	6 oz..	Scholle QC	40" H x 33" W x 23.6" D (101.6cm H x 83.8cm W x 59.9cm D)	225 lbs. (102.1 kg)	See chart above.	No	 
	40800.0001			Scholle 1910					
	40800.0002			QCD-II					


Liquid Coffee Ambient Dispensers (LCA-2 only)



LCA-2, IC

Coffee-On-Demand dispenser meets the requirements of banquets, convention centers, and hotels

LCA-2, LCA-2 IC

- Accommodates all ½ gallon (1.9 litre) and most one gallon (3.8 litre) BIB containers.
- Insulated product cabinet.
- Convenient flip tray for dispensing into decanters or carafes.
- Compatible with BUNNlink®. 

LCA-2

- Global multi-volt design is easily converted to ratings from 100 to 240 volts (50-60 hertz).
- FlavorGard® technology continuously monitors extract-to-water ratio.
- Easy-to-program one touch portion control model is available for self-serve applications.
- Equipped with tank drain.

LCA-2 IC



- Connects to ambient water supply for a final coffee beverage served over ice.



LCA-2



LCA - PC
(LCA is also available with portion control)


Model	Product #	Dispense Rate/Sec.		Connector Type	Volts	Amps	Watts	Capacity	Dimension	Weight	Cord Attached	Agencies	
		1.8 oz..	2.5 oz..*										
		Product Ratios											
LCA-2, IC	37700.0000	25:1 - 100:1		Scholle 1910LX	120	2	240	810 cups	30" H x 12.2" W x 24.9" D (76.2cm H x 31cm W x 63.3cm D)	83 lbs. (37.2 kg)	Yes		
LCA-2	34400.0001												
	34400.0002	25:1 - 45:1	25:1 - 65:1										
	34400.0003	45:1 - 100:1	65:1 - 100:1	LiquiBox QC/D II									
	34400.0004	25:1 - 45:1	25:1 - 65:1										
All models can be changed to these electrical configurations.					208	22.6	4700	385 cups			No		
					240	25.8	6200	512 cups					
LCA-2, PC	36500.0001	45:1 - 100:1	65:1 - 100:1	Scholle 1910LX	120	14.2	1700	125 cups			Yes		
	36500.0002	25:1 - 45:1	25:1 - 65:1										
	36500.0003	45:1 - 100:1	65:1 - 100:1	LiquiBox QC/D II									
	36500.0004	25:1 - 45:1	25:1 - 65:1										
All models can be changed to these electrical configurations.													208
					240	25.8	6200	512 cups					

Liquid Coffee Refrigerated Dispensers



LCR-2





Coffee-On-Demand dispenser meets the requirements of banquets, convention centers, and hotels

- Refrigerated product cabinet maintains 38 – 42° F (3 – 55° C) in product compartment.
- Accommodates all ½ gallon (1.9 litre) and most one gallon (3.8 litre) BIB containers.
- Convenient flip tray allows for dispensing into decanters or carafes.
- Global multi-volt design is easily converted to ratings from 100 to 240 volts (50-60 hertz).
- FlavorGard® technology continuously monitors extract-to-water ratio.
- Easy-to-program one touch portion control model is available for self-serve applications.
- Equipped with tank drain.
- Compatible with BUNNlink®. 



LCR - PC

(LCR is also available with portion control)

Model	Product #	Dispense Rate/Sec.		Connector Type	Volts	Amps	Watts	Capacity	Dimension	Weight	Cord Attached	Agencies			
		1.8 oz..	2.5 oz.*												
		Product Ratios													
LCR-2	34400.0036	45:1 - 100:1	65:1 - 100:1	Scholle	120	14.2	1700	125 cups	38" H x 12.2" W x 24.9" D (96.5cm H x 31cm W x 63.2cm D)	114 lbs. (51.7 kg)	Yes	 			
	34400.0037	25:1 - 45:1	25:1 - 65:1												
	34400.0038	45:1 - 100:1	65:1 - 100:1	LiquiBox QC/D II											
	34400.0039	25:1 - 45:1	25:1 - 65:1												
All models can be changed to these electrical configurations.					208	25.8	4100	385 cups			No				
					240		6200	512 cups							
LCR-2, PC	36500.0036	45:1 - 100:1	65:1 - 100:1	Scholle	120	14.2	1700	125 cups			38" H x 12.2" W x 24.9" D (96.5cm H x 31cm W x 63.2cm D)		114 lbs. (51.7 kg)	Yes	 
	36500.0037	25:1 - 45:1	25:1 - 65:1												
	36500.0038	45:1 - 100:1	65:1 - 100:1	LiquiBox QC/D II											
	36500.0039	25:1 - 45:1	25:1 - 65:1												
All models can be changed to these electrical configurations.					208	25.8	4700	385 cups						No	
					240		6200	512 cups							

Liquid Coffee Low Profile Dispensers



LCA-2 LP

Coffee-On-Demand dispenser meets the requirements of banquets, convention centers, and hotels



- Attractive appearance with shorter profile.
- Dispense over 120 (5 oz.) cups per hour.
- Accommodates two .5 gallon BIB containers.
- Serves two coffee products and hot water.
- LED lights alert when more concentrate is needed.
- Rinse LED lights alert when cleaning is needed.
- Set up for continuous dispense (*by the cup*) for self-serve applications or portion-control to fill cups or carafes.

LCC-2 LP

- Chilled product cabinet utilizes thermoelectrics for optimal performance.
- Accommodates two .5 gallon BIB containers sized approximately 7.5"H x 5.25"W x 4"D.



LCC-2 LP

Model	Product #	Dispense Rate/Sec.	Connector Type	Dimension	Weight	Volts	Amps	Watts	Capacity	Cord Attached	Agencies
		1.7 oz. Product Ratios									
LCC-2, LP	38800.0004	25:1 - 100:1	Scholle 1910LX	23.2" H x 15.8" W x 20.9" D (58.9cm H x 40.1cm W x 53cm D)	65 lbs. (29.5 kg)	120	12	1440	120 cups	Yes	 
	38800.0005		QCDII								
	38800.0006		Scholle Q/C								
	38800.0007		Rapak								
LCA-2, LP	38800.0000		Scholle 1910LX								
	38800.0001		QCDII								
	38800.0002		Scholle Q/C								
	38800.0003		Rapak								