

Airpot Coffee Brewer

Features

Airpot Coffee Brewer

- Brews directly into 1.9 to 3 litre airpots.
- Convenient airpots keep coffee hot and fresh for hours.
- Airpots are easily transported to remote meeting rooms, breakfast bars, etc.
- Pourover model available (CW-APS).
- Pourover feature included on automatic models.
- Gourmet funnel model available for use with heavier throw weights of coffee.
- Digital timer enables users to make brew cycle adjustments from the front panel.
- Brew capacity varies by model. See back for details.



CWTF APS with Airpot

(airpot sold separately)

Dimensions: 23.6" H x 9" W x 18.5" D
(59.9cm H x 22.9cm W x 47cm D)

For current specification sheets and other information, go to www.bunn.com.

International models may vary in appearance.

Related Products

Easy Clear® EQ-17-TL
Product No. : 30200.1000



Easy Clear® ED-17-TL
Product No. : 30201.1001

Paper Filter Pack
Product No. : 20115.0000



2.2 liter Push-Button Airpot
Product No. : 28696.0002



2.5 liter Push-Button Airpot
Product No. : 13041.0001

2.5 liter Lever-Action Airpot
Product No. : 32125.0000

3.0 liter Lever-Action Airpot
Product No. : 32130.0000



Universal Airpot Racks
for push-button and lever-action airpots.



Gourmet C Funnel
Product No.: 34559.0000
(18.1cm width)

34559.0001 (19.4cm width)



Dimensions & Specifications

Model	Product #	Volts	Amps	Tank Heater Watts	Total Watts	Brewing Capacity	Shipping Weight	Cord Attached	Agency
CWA-APS*	23001.0024	230	9.1	1320	2100	5.2 gal./hr.	28 lbs.	No	CE V P G NSF
Power cord	27728.0001					(19.7 L./hr.)	(12.7 kg)		
CWTFA-APS	23001.0021	230	9.1	1320	2100	5.1 gal./hr.	37 lbs.	No	CE V P G NSF
Power cord	27728.0001					(19.3 L./hr.)	(16.8 kg)		
CWTFA35-APS	23001.0019	230	14.2	1320	3280	5.1 gal./hr.	37 lbs.	No	CE V P G NSF
Power cord	27728.0001					(19.3 L./hr.)	(16.8 kg)		
CWA-APS**	23001.0079	230	9.1	1850	2100	3.8 gal./hr.	26 lbs.	No	CE NSF
Power cord	27728.0001					(14.4 L./hr.)	(12.7 kg)		
CWA-APS	23001.0064	220	8.6	1850	1900	3.8 gal./hr.	26 lbs.	No	↻
Power cord	27728.0001					(14.4 L./hr.)	(12.7 kg)		
CWA-APS	23001.0074	230	9.1	1850	2100	3.8 gal./hr.	26 lbs.	Yes	CE NSF
						(14.4 L./hr.)	(12.7 kg)	UK Plug	
CWTFA35-APS	23001.0065	220	13.6	2940	3000	7.5 gal./hr.	33 lbs.	No	↻
Power cord	27728.0001					(28.4 L./hr.)	(15 kg)		
CWTFA-APS	23001.0066	220	8.6	1850	1900	5.1 gal./hr.	37 lbs.	No	↻
Power cord	27728.0001					(19.3 L./hr.)	(16.8 kg)		

*Pourover model. **Gourmet funnel


Airpot sold separately.

Brewing capacity: based upon incoming water temp of 60°F/15.5°C (140°F/60°C rise) per 1/2 gallon brew time of 4 minutes.

Electrical: 230V model requires 2 wires plus ground service rated 220-240V, single phase, 50/60 Hz.

220V model requires 2 wires plus ground service rated 220-240V, single phase, 60Hz.

Plumbing: 20-90 psi (138-621 kPa). Supplied with 1/4" male flare fitting.



BUNN Corporation - 1400 Stevenson Drive Springfield, Illinois 62703 • USA • +1-217-529-6601 • Fax +1-217-529-2827 • www.bunn.com

BUNN® practices continuous product research and improvement. We reserve the right to change specifications and product design without notice. Such revisions do not entitle the buyer to corresponding changes, improvements, additions or replacements for previously purchased equipment.

All dimensions shown in centimeters. Bunn Corporation owns all copyrights relating to materials in this publication. Please contact Bunn Corporation to request permission to reproduce any portion of this publication.