

# BUNN®

## Twin 3 Gallon Automatic Electric Coffee Urn

ITEM#

PROJECT

DATE



### Model U3\*

Dimensions: 32.4" H x 34.5" W x 21" D  
(82.3cm H x 87.6cm W x 53.3cm D)

### Features

#### Automatic Electric Coffee Urn

- Brews 16.3 to 18.8 gallons (61.7 to 71.2 litres) of perfect coffee per hour.
- Unique design assures extremely low evaporation loss to maintain the brew at its flavorful peak.
- Large water tank—over 20 gallons.
- Draw off hot water during brewing cycle without affecting coffee quality.
- Half-batch option.
- Top mounted components for ease of service.
- All stainless steel construction.
- International electrical configurations available.

For current specification sheets and other information, go to [www.bunn.com](http://www.bunn.com).

\* International models may vary in appearance.

### Related Products

#### Easy Clear® EQHP-10

Product No. : 39000.0004



#### Easy Clear® EQHP-10L

Product No. : 39000.0001

#### Easy Clear® EQHP-25

Product No. : 39000.0005



#### Easy Clear® EQHP-25L

Product No. : 39000.0002

#### SRU Paper Filters

Product No. : 20109.0000

Packed per case: 250

Dimensions: 7" Base x 5 1/4" Sidewall

17.78 cm Base x 13.34 cm Sidewall



#### Easy Pour® black decanter

Product No. : 06100.0101

Quantity: 1

(also packaged in quantities of 2, 3, 6, 12, & 24)



#### Easy Pour® orange decanter (for decaf)

Product No. : 06101.0101

Quantity: 1 (also packaged in quantities of 2, 3, 6, 12, & 24)

#### U3 Drip Tray (Optional)

Product No. : 07284.0000

All Stainless Steel



Model

Agency Listing

U3



Patents Apply

11/09

A4.2

## Dimensions & Specifications

Model	Product #	Volts	Amps	Tank Heater Watts	Total Watts	Brewing Capacity	Cu. Ft.	Shipping Weight	Cord Attached
U3 (SS)	20500.0000	120/208	28	5750	5825	16.3 gal./hr.	18	103 lbs.	No
U3 (SS)	20500.0001	120/240	28	6650	6725	18.8 gal./hr.	18	103 lbs.	No

Note: SS=Single Service

**Brewing capacity:** based upon incoming water temp of 60°F (140°F rise) per 1/2 gallon brew time of 4 minutes.

Models listed as 120/208V or 120/240V must be connected to 208V or 240V electrical service respectively. Please refer to the installation manual.

Electrical: Model requires 3-wires plus ground service rated 120/240V, single phase, 60 Hz.

Plumbing: 20-90 psi (138-621 kPa). Supplied with 3/8" OD male flare fitting.

