

# BUNN®

## Dual Soft Heat® Brewer with Docking System

ITEM#

PROJECT

DATE



**Model Dual SH with  
1.5 gallon SH Servers**  
(servers sold separately)

Dimensions: 35.8" H x 18" W x 20.5"D  
(91cm H x 45.7cm W x 52.1cm D)

### Features

#### Coffee brewers with portable servers

- Brews 16.3 to 18.9 gallons (61.7 to 71.5 litres) of perfect coffee per hour.
- Brews ½, 1, or 1½ gallon (1.9, 3.8 or 5.7 litre) batches.
- Patented server heat control automatically shuts off once target temperature is reached. Can be set to 175°–190°F (79.4–87.8°C).
- Electronic grinder interface instructs grinder on exact amount of coffee for selected brew batch size.
- Remote 1 or 2 server docking stations for additional satellite coffee serving.
- Safety-Fresh® patented brew-through lid with vapor seal and spill prevention.
- Variable batch selector knob lets you brew large batches or small servings.
- International electrical configurations available.

For current specification sheets and other information, go to [www.bunn.com](http://www.bunn.com).

### Related Products

**Easy Clear® EQHP-25L**  
Product No. : 39000.0002



**Easy Clear® EQHP-25**  
Product No. : 39000.0005

**Single/Dual Filter Pack**  
Product No. : 20138.0000  
Packed per case: 500  
Dimensions:  
5¼" Base x 4¼" Sidewall  
13.3 cm Base x 10.8 cm Sidewall



**SH Server**  
Product No.: 27850.0001



**Two Position Drip Tray**  
Product No.: 27150.0000



**2SH Stand**  
Product No.: 27875.0000



#### Model

Dual SH

#### Agency Listing



Patents Apply

9/08

A2.7

## Dimensions & Specifications

Model	Product #	Volts	Amps	Tank Heater Watts	Total Watts	Capacity	Cubic Measure	Shipping Weight	Cord Attached
Dual SH Brewer	27900.0001	120/208	28.9	2@2850	5900	16.3 gal./hr.	13.3 ft <sup>3</sup>	90 lbs.	No
Dual SH Brewer	27900.0002	120/240	29.1	2@3300	6800	18.9 gal./hr.	13.3 ft <sup>3</sup>	89 lbs.	No
Dual SH Brewer*	27900.0020	120/208	29.1	2@3300	5900	18.9 gal./hr.	13.3 ft <sup>3</sup>	90 lbs.	No
SH Server(1.5 gal.)	27850.0001	n/a	n/a	n/a	n/a	1½ gal.	2.4 ft <sup>3</sup>	17 lbs.	No
SH Server*(1.5 gal.)	27850.0004	n/a	n/a	n/a	n/a	1½ gal.	2.4 ft <sup>3</sup>	18 lbs.	No
1SH Stand	27825.0000	120	.8	n/a	90	1 SH Server	1.2 ft <sup>3</sup>	13 lbs.	Yes
1SH Stand*	27825.0004	120	.8	n/a	90	1 SH Server	1.2 ft <sup>3</sup>	13 lbs.	Yes
2SH Stand	27875.0000	120	1.5	n/a	180	2 SH Servers	2.1 ft <sup>3</sup>	22 lbs.	Yes
2SH Stand*	27875.0003	120	1.5	n/a	180	2 SH Servers	2.1 ft <sup>3</sup>	22 lbs.	Yes

\*Models have black finish.

**Note:** Soft Heat® Brewers and Servers are boxed and shipped separately. All brewers have mechanical thermostats.

**Brewing capacity:** based upon incoming water temp of 60°F/15°C (140°F/60°C rise) per ½ gallon brew time of 4 minutes.

Models listed as 120/208V or 120/240V must be connected to 208V or 240V electrical service respectively. Please refer to the installation manual.

Electrical: Brewer is 3-wires plus ground service rated 120/208V or 120/240V, single phase, 60Hz.

Plumbing: 20-90 psi (138-621 kPa). Machine supplied with ¼" male fitting. Tank capacity: 8.4 gallons (31.8 L)

