

Titan[™] Dual Brewer

Features

Titan Dual Brewer

High-volume brewing solution that features simple operation, precise extraction control and portable servers

- Brews up to 31.8 gallons (120 litres) of perfect coffee per hour.
- Coffee extraction controlled with pre-infusion and pulse brew, digital temperature control, and large sprayhead; coffee strength controlled with variable by-pass.
- BrewMETER[®] allows automatic programming of pulse routine.
- SplashGard[®] funnel and funnel locks help improve safety.
- Funnel has 28 ounce (.8 kg) ground coffee capacity and paper filter retainers to eliminate fold-over.
- Titan TF servers are insulated to keep coffee hot for hours.
- Hot water faucet.
- 3-phase or single-phase operation.
- Energy-saver mode reduces tank temperature during idle periods.



Model Titan Dual Brewer with 3 gallon (12 litres) TF Servers *(servers sold separately)*

Dimensions: 40.02" H x 35.63" W x 21.74" D
(101.7cm H x 90.5cm W x 55.2cm D)

For current specification sheets and other information, go to www.bunn.com.

Related Products

Easy Clear[®] EQHP-54
Product No. : 39000.0006



Easy Clear[®] EQHP-54L
Product No. : 39000.0003

Titan/Urn Filter Pack
Product No. : 20111.0000
Packed per case: 250
Dimensions:
20" Base x 8" Sidewall
50.8 cm Base x 20.3 cm Sidewall



Titan TF Server
Product No.: 39400.0001
3 gallon (12 litres)



Titan Funnel
Product No.: 40114.0000



Dimensions & Specifications

Model	Product #	Volts	Amps	Total Watts	Brewing Capacity	Shipping Weight	Funnel Locks	Cord Attached	Agency
Titan Dual	39200.0002	230/400	16	11125	31.8 gal/hr (120 l/hr)	148 lbs. (67.1 kg)	Yes	No	CE
		(3-phase) 230* (1-phase)	33.5	8000	21.3 gal/hr (80 l/hr)				
Titan Dual	39200.0003**	200 (3-phase)	24.3	8400	24 gal/hr (91 l/hr)	148 lbs. (67.1 kg)	Yes	No	

Brewing capacity: based upon incoming water temp of 15°C (78°C rise).

*Brewer can easily be rewired in the field for single-phase operation.

Electrical: Brewer is 4-wires plus ground service rated 230/400V, 3-phase, 50/60Hz.

*Brewer is 3-wires plus ground service rated 230V, 1-phase, 50/60Hz.

**Brewer is 3-wires plus ground service rated 200V, 3-phase, 50/60Hz.

Plumbing: 20-90 psi (138-621 kPa). Machine supplied with $\frac{3}{8}$ " male flare fitting, and back-flow prevention.
4 gal/min (15.2 l/min) requirement. Tank capacity: 14 gallons (53 L)

