



PROJECT	
ITEM #	
QUANTITY	DATE
APPROVAL	

SALD-1/SALD-2

Salad and Vegetable Drier

Short Form Specifications

Outer body is constructed of 18-gauge stainless steel. Legs are 1" (2.54cm) outside diameter, 16-gauge stainless steel tubing with 4" (10.16 cm) diameter locking stem casters for mobility.

Outer lid is constructed of 18-gauge stainless steel.

Inner liner is a one-piece durable polyethylene plastic with 3/8" (.95cm) diameter holes for proper water disbursement.

Unit has a completely enclosed, water-tight motor mounted underneath the unit. Electrical box for capacitor and timer control is mounted on the bottom of the unit. Six foot cord and 5-15 NEMA plug are supplied.

Unit has a 1.5" (3.81cm) outside diameter drain, and an adjustable on/off timer for selection of drying cycles of up to five minutes.

Stainless steel hooks are mounted on the lid and sides of the unit for storage of the lid and cord when unit is not in use.

Optional Accessories and Modifications

- 220 volt electrical system - SALD-2
- Additional polyethylene liner



Model SALD-1



Mechanical Data—Standard Unit

MODEL NUMBER	UNIT HEIGHT	UNIT WIDTH	UNIT DEPTH	INNER LINER CAPACITY	INNER LINER DIAMETER	INNER LINER DEPTH	VOLTS	AMPS	SHIP WEIGHT
SALD-1	32.5" (82.6cm)	27" (68.6cm)	27" (68.6cm)	20 Gal (77L)*	15.62" (39.7cm)	16.87" (42.9cm)	115 v	2.7	85 lbs/ 38 kg
SALD-2	32.5" (82.6cm)	27" (68.6cm)	27" (68.6cm)	20 Gal (77L)*	15.62" (39.7cm)	16.87" (42.9cm)	220 v	1.35	85 lbs/ 38 kg

*Inner liner can hold up to 18 heads of chopped lettuce.

The Delfield Company, 980 S. Isabella Rd., Mt. Pleasant, MI 48858, U.S.A. • (800) 733-8821 • Fax (800) 669-0619 • www.delfield.com

Delfield reserves the right to make changes in design or specifications without prior notice. ©2002 The Delfield Company. All rights reserved. Printed in U.S.A.

MSSALD 10/01