Shelleyspeed Model by Delfield

Project		
Item		
Quantity		
CSI Section 11400		

SPM-W

Utility (Merchandising) Module, 34" height, 35" depth

MODELS

□ SPM-28W 28" length, merchandising module, 34" height, 35" depth

□ SPM-60W

60" length, merchandising module, 34" height, 35" depth

☐ SPM-36W

36" length, merchandising module, 34" height, 35" depth

☐ SPM-74W

74" length, merchandising module, 34" height, 35" depth

☐ SPM-50W

50" length, merchandising module, 34" height, 35" depth

STANDARD FEATURES

- 14-gauge stainless steel tops standard
- 34" counter height, 35" depth
- 18-gauge stainless steel exterior body
- Units have a single or double door dry compartment for storage
- Standard on 5" diameter polyurethane swivel casters
- Stainless steel fully retractable interlock provided as standard
- A wide selection of laminate colors available at no additional charge
- Laminate selection has 18-gauge galvanized base,
 16-gauge coved corner supports to protect laminate
- Meets NSF standards
- One-year parts and 90 day labor standard warranty.
 Additional warranties available.

OPTIONS AND ACCESSORIES

- Single tier merchandiser (Unheated)Double tier merchandiser (Unheated)
- ☐ 16"x35" Stainless steel drop tray shelf
- Stainless steel cash shelf
- lacksquare Tray slides
 - V-style
 - Tubular bar
- Decal package
- □ Canopy
- Basket storage rack for base of unit
- ☐ Lid storage rack for base of unit



SPECIFICATIONS

Exterior: Exterior body is constructed of 18-gauge stainless steel side panels or 18-gauge galvanized reinforced laminate panels. 14-gauge galvanized bottom. All exterior side panels are reinforced with overlapping corners and are welded in place. All insert cutouts are reinforced with 14-gauge galvanized channel supports.

SPM-50W

Exterior top is constructed of 14-gauge stainless steel, welded, ground and polished into one integral unit. Top is fabricated with square exterior corners with fully hemmed nosing on all sides. Stainless steel fully retractable interlocks are installed on opposing corners and locks units into a complete serving system.

Units have a one or two door dry compartment(s) constructed of 18-gauge stainless steel. All doors have recessed black ABS door handle as standard. Door(s) are double-wall construction, with stainless steel front panel.

Casters: Unit is mounted on 5" (12.7cm) diameter swivel polyurethane casters with non-marking tires and plate brakes. Casters are bolted directly to the 14-gauge bottom of the base. Overall height of caster assembly is 6.00" (15.2cm).

Styling: Units are standard with 18-gauge stainless steel exterior sides. Laminate is an option available at no additional charge. Decal packages and canopies are also available.




980 S. Isabella Road Mt. Pleasant, MI 48858 www.delfield.com Phone: 800-733-8948 Fax: 800-669-0619 Email: info@delfield.com Approval ______


SPM-W SHELLEYSPEED™ UTILITY (MERCHANDISING) MODULE, 34"HEIGHT, 35" DEP





Model #_ CSI Section 11400

SPM-W - Utility Merchandising Module, 34" height, 35" depth










Plan View SPM-28W

Plan View SPM-36W

Plan View SPM-50W


Plan View SPM-60W




Plan View SPM-74W




Elevation View SPM-28W




Elevation View SPM-36



Elevation View SPM-50W




Elevation View SPM-60W



Elevation View SPM-74W

*If ordering optional basket or lid storage module.



III VIII III I	INE PAIN	- PAIA				
MODEL NUMBER	ТҮРЕ	L	D	н	NUA DO	
SPM-28W	UTILITY MODULE	28	35	34		
SPM-36W	UTILITY MODULE	36	35	34		
SPM-50W	UTILITY MODULE	50	35	34		
SPM-60W	UTILITY MODULE	60	35	34		

MECHANIC	MECHANICAL DATA:									
MODEL NUMBER	TYPE	L	D	н	NUMBER OF DOORS	BASKET CAPACITY (BASE OF UNIT)*	LID STORAGE CAPACITY (BASE OF UNIT)*	SHIP WEIGHT		
SPM-28W	UTILITY MODULE	28	35	34	1	8 (13.25X26.13X2.5) 4 (13.25X26.13X4.75)	NA	165		
SPM-36W	UTILITY MODULE	36	35	34	1	8 (13.25X26.13X2.5) 4 (13.25X26.13X4.75)	NA	185		
SPM-50W	UTILITY MODULE	50	35	34	2	16 (13.25X26.13X2.5) 8 (13.25X26.13X4.75)	14	205		
SPM-60W	UTILITY MODULE	60	35	34	2	24 (13.25X26.13X2.5) 12 (13.25X26.13X4.75)	14	250		
SPM-74W	UTILITY MODULE	74	35	34	2	24 (13.25X26.13X2.5) 12 (13.25X26.13X4.75)	14	270		



980 S. Isabella Road Mt. Pleasant, MI 48858 Phone: 800-733-8948 Fax: 800-669-0619 Email: info@delfield.com Printed in the USA. 06/05 **SSSPMW**

Delfield reserves the right to make changes in design or specifications without prior notice.