



Specification Line®

Self-Contained Solid Door Shallow Reach-In Freezer

Project _____
Item _____
Quantity _____
CSI Section 11400
Approved _____
Date _____

Models

One section	Two section	Three section	
SSF1S-S	SSF2S-S	SSF3S-S	Stainless exterior and interior full door
SSF1S-SH	SSF2S-SH	SSF3S-SH	Stainless exterior and interior half door
SAF1S-S	SAF2S-S	SAF3S-S	Stainless exterior and aluminum interior full door
SAF1S-SH	SAF2S-SH	SAF3S-SH	Stainless exterior and aluminum interior half door
SMF1S-S	SMF2S-S	SMF3S-S	Stainless front aluminum exterior and interior full door
SMF1S-SH	SMF2S-SH	SMF3S-SH	Stainless front aluminum exterior and interior half door



SSF2S-SH

Standard Features

- Stainless steel interior and exterior (SS)
- Stainless steel exterior, aluminum interior (SA)
- Aluminum interior and exterior, stainless front (SM)
- Built in door locks with heavy duty strikes
- Recessed metal door handle
- Pressure relief valve is standard to prevent door vapor lock
- Exterior digital thermometer with high/low temperature alarm
- Easy to use electronic control
- Easy access "flip up" shroud
- Three wire shelves per section - SA/SS standard with chrome plated shelves and SM standard with epoxy coated shelves
- Tough ABS interior door liners
- 10' attached cord and plug on 115V units
- 6" adjustable stainless steel legs
- Stainless steel breaker strips
- High density foamed in place environmentally friendly, Kyoto Protocol Compliant, Non ODP (Ozone Depletion Potential), Non GWP (Global Warming Potential) polyurethane keeps energy costs low
- Energy savings door heater switch
- Two year parts & labor warranty
- Five year compressor warranty

Options & Accessories

- Security (prison) package
- 6" polyurethane casters
- Door field rehingability
- Stainless steel interior door liner
- Additional shelves
- Stainless steel back
- Laminate on front, sides and back
- Bottom mount electrical
- Stainless steel banking strip
- Heat shield end
- Stainless steel kick plate
- Laminate kick plate
- 4" stainless steel utility base
- 230-50-1 electrical
- 220-60-1 electrical

Specifications

Exterior: SS and SA models shall have corrosion resistant stainless steel exterior cabinet sides, front and shroud. SM models shall have corrosion resistant aluminum on exterior cabinet sides and will have stainless front and shroud. All units shall have the upper shroud hinged with a gas assist stay open feature to provide easy access to the refrigeration system.

Interior: Cabinet interior shall be corrosion resistant stainless steel (SS models) or heavy gauge aluminum (SA and SM models). Bottom and top surfaces shall be die stamped to provide radius corners and recessed floor. Three wire shelves are provided per section, SA/SS standard shelves are chrome plated, SM standard shelves are epoxy coated. Shelves rest on clips which are adjustable on 1" increments on stainless steel pilasters affixed to the cabinet interior. Pilasters are removable without tools for cleaning. Mounted to the interior ceiling, the interior incandescent light is controlled automatically through a switch mounted in the hinge assembly to protect against breakage. Door openings are protected with heavy gauge stainless steel breaker strips. An air duct shall be mounted to the ceiling assuring low velocity, even air movement throughout the cabinet interior.

Doors: Exterior shall be corrosion resistant stainless steel. Interior liner shall be resilient high impact ABS material formed to protrude beyond the door gasket to protect the gasket from tearing. Each door has two edge mount, self closing, cam lift style hinges. Doors can be removed from the cabinet without the use of tools. Metal


door handle shall be recessed into the door for easy grip without impacting aisle space. Keyed door lock is mounted in the door next to the handle. Lock engages into a heavy duty strike mounted to the cabinet face. Door gaskets are magnetic and mount to the door snapping in place and are removable without tools.

Refrigeration system: All components are mounted to the exterior of the cabinet ceiling, outside the food zone and are assembled as one piece and can be removed as one piece. Environmentally friendly R404A refrigerant is used. The system has the capability of maintaining between -5°F and 0°F in heavy use food service operations. Refrigerant is metered using a highly responsive thermostatic expansion valve. System is controlled using Delfield's ACT-Advanced Control Technology electronic temperature control, which provides improved pull down times, reduces compressor cycling and longer compressor life with lower energy consumption.


Control system uses adaptive defrost to assure evaporator coil is free of ice and is operating at optimum efficiency. Evaporator condensate is eliminated using an energy efficient hot gas system.

Electrical: Standard electrical on one and two section units shall be 115V, 60 Hz single phase. A 10' cord and plug is supplied and attached to a junction box mounted on the exterior top of the cabinet. Three section units shall be 115/208-230 and will require hardwire connections.







PLAN VIEW
SSF15-S, SAF15-S, SMF15-S
SSF15-SH, SAF15-SH, SMF15-SH




PLAN VIEW
SSF25-S, SAF25-S, SMF25-S
SSF25-SH, SAF25-SH, SMF25-SH




PLAN VIEW
SSF35-S, SAF35-S, SMF35-S
SSF35-SH, SAF35-SH, SMF35-SH




ELEVATION VIEW
SSF15-S, SAF15-S, SMF15-S




ELEVATION VIEW
SSF15-SH, SAF15-SH, SMF15-SH




ELEVATION VIEW
SSF25-S, SAF25-S, SMF25-S




ELEVATION VIEW
SSF25-SH, SAF25-SH, SM25-SH



ELEVATION VIEW
SSF35-S, SAF35-S, SMF35-S



ELEVATION VIEW
SSF35-SH, SAF35-SH, SMF35-SH



END VIEW
ALL MODELS

Mechanical Data

MODEL NUMBER	VOLTAGE	AMPS	STORAGE CU.FT.	SHELVES SQ.FT.	NO. OF SHELVES	UNIT H.P.	BTU/HR SYSTEM CAP	SHIP WEIGHT	NEMA PLUG	ENERGY (KWH)
SSF15-S, SSF15-SH, SAF15-S, SAF15-SH, SMF15-S, SMF15-SH	115	7.8	18.25	8.98	3	1/2	1516	406lbs (184kg)	5-15P	8.04
SSF25-S, SSF25-SH, SAF25-S, SAF25-SH, SMF25-S, SMF25-SH	115	11.5	37.96	19.04	6	3/4	1923	676lbs (307kg)	5-15P	10.55
SSF35-S, SSF35-SH, SAF35-S, SAF35-SH, SMF35-S, SMF35-SH	115/208-230	11.5	57.67	29.10	9	1	4793	909lbs (412kg)	N/A	19.78

Delfield reserves the right to make changes to the design or specifications without prior notice.