



# H55 and H55-2 High Efficiency Gas Fryers

Project \_\_\_\_\_  
 Item \_\_\_\_\_  
 Quantity \_\_\_\_\_  
 CSI Section 11400 \_\_\_\_\_  
 Approval \_\_\_\_\_  
 Date \_\_\_\_\_

## Models

☐ H55  
☐ H55-2

☐ H55C  
☐ H55-2C

☐ H55BL  
☐ H55-2BL

☐ H55BLC  
☐ H55-2BLC



Shown with optional  
CM3.5 controller and casters

## Standard Features

- Open-pot design (split or full) is easy to clean
- 50-lb (25 L) oil capacity
- 80,000 Btu/hr. input (20,151 kcal) (23.4 kw) full pot; 40,000 Btu/hr. input (10,075 kcal) (11.7 kw)
- Analog controller
- Center-mounted, RTD, 1° compensating temperature probe
- Deep cold zone with forward-sloping bottom and 1-1/4" IPS full-port, ball-type drain valve
- Infrared burners ensure state-of-the-art heat transfer
- Stainless steel frypot and door, enamel cabinet
- Electronic ignition
- Automatic melt cycle and boil-out mode
- Two twin baskets
- 8-1/2" (22.0 cm) legs

## Options & Accessories

- ☐ Built-in filtration available on single frypot fryers except H155-2 (single split frypot) for CE
- ☐ Built-in filter available on single frypot fryers including a spreader cabinet and on multiple frypot batteries -- 2 to 6 fryers can be battery to right side of filter
- ☐ External oil discharge -- available on two or more frypots or one frypot and spreader with filtration -- must specify front or rear connection
- ☐ CM3.5 controller, electronic timer/controller or digital controller
- ☐ Automatic basket lifts (units with basket lifts require casters to be purchased also)
- ☐ Spreader cabinet with flat top or holding station
- ☐ Frypot cover
- ☐ Casters

See Frymaster domestic price list for other available options and accessories.

## Specifications

### Specifically designed for high capacity, reliability, versatility and efficiency

Frymaster's H55 is a premium open-pot fryer that combines state-of-the-art technology with decades of frying experience and customer satisfaction to set the standard for high-efficiency frying. The ENERGY STAR® rated H55 fryer saves thousands of dollars annually on energy costs. H55 fryers have long been the trusted choice of chains and independent operators worldwide because their efficient, state-of-the-art heat transfer system, precise controls and durability have stood the test of time.


Infrared burners and blower system delivers an ultra-refined air-gas mixture so the fryer operates well in any gas application such as at high altitudes, in environments where air circulation is sub-optimal or when the heating value of the gas is diminished.

The H55 has a maximum 50-lb. (25 liter\*) oil capacity. The frying area is 14" x 15" (35.6 x 38.1 cm) and heating input is 80,000 Btu/hr (20,151 kcal) (23.4 kw).

Each side of the H55-2 split-pot fryer operates on 40,000 Btu/hr. (10,076 kcal/hr) (11.7 kw) has a frying area of 6-1/2" x 15" (16.5 x 38.2 cm). The split-pot model has all of the features and options of the full-pot H55 and gives the operator the discretion of using only half the fryer.

The optional spreader cabinet can include a holding station with heat lamp option. The holding stations are available with cafeteria-style pan or scoop-type pan.

\*Liter conversions are for liquid shortening @70°F.



H55-2

H55

Unique frypot design with deep cold zone and turbocharged, infrared burners.



Approved for  
Australia


8700 Line Avenue  
 Shreveport, LA 71106-6800  
 USA

Tel: 318-865-1711  
 Tel: 1-800-221-4583  
 Fax: 318-868-5987  
 E-mail: info@frymaster.com

www.frymaster.com  
 Bulletin No. 818-0499  
 Printed 9/09  
 Revised 8/25/11



H55 and H55-2 High Efficiency Gas Fryers



## DIMENSIONS

MODEL NO.	OIL CAPACITY	OVERALL SIZE (cm)			DRAIN HEIGHT (cm)	NET WEIGHT	SHIPPING INFORMATION					
		HEIGHT	WIDTH	LENGTH			WEIGHT	CLASS	CU. FT.	DIMENSIONS (cm)		
H55	50 lbs. (25 L)	45-5/8"*	15-5/8"	29-5/8"*	10-1/4"	160 lbs. (73 kg)	202 lbs. (92 kg)	85	21.32	H	W	L
H55-2	25 lbs. (12 L) ea. side	(115.8)	(39.7)	(75.3)	(26.1)					46-1/2"	22"	36"
										(118.1)	(55.9)	(91.4)

\*Without basket lifts.

## POWER REQUIREMENTS, PER FRYPOT

MODEL NO.	BASIC DOMESTIC OPTIONS		
	CONTROLLER	FILTER	BASKET LIFTS
H55	120V 1 A	120V 8 A	120V 3 A
H55-2	220V 1 A	220V 5 A	220V 2 A
	BASIC EXPORT/CE OPTIONS		
	220V/250V 1 A	220V/250V 5 A	220V/250V 2 A
H55			
H55-2			

## HOW TO SPECIFY

The following description will assist with ordering the features desired for this equipment:

H55	50-lb. (25 L) high-efficiency, open-pot gas fryer with, analog controller, electronic ignition, melt cycle, boil-out mode and center-mounted (RTD) 1° compensating temperature probe
H55-2	Split pot with same features as full pot plus dual controls to operate each split pot independently
C	CM3.5 controller
BL	Basket Lifts
SD	Stainless steel frypot and door -- enamel cabinet
SC	Stainless steel frypot, door and cabinet

## NOTES:

- 120 V 5 ft. (1.5 m) grounded cord set provided.
- Recommended minimum store supply pressure to be 6" W.C. for NAT Gas, and 11" W.C. for L.P. Check plumbing codes for proper supply line sizing to attain burner manifold pressure of 3.0" W.C. natural or 8.25" W.C. L.P. Incoming supply line should be 1-1/2" (3.8 cm). Should flexible gas line be used, it must be AGA approved, commercial type and sized per the gas line size in above drawing.

## CLEARANCE INFORMATION

A minimum of 24" (61.0 cm) should be provided at the front of the unit for servicing and proper operation, and 6" (15.2 cm) between the sides and rear of the fryer to any combustible material.