



## Specifications

**Finish:** Exclusive all stainless steel base with radiused corners improves sanitation and durability. Other stainless steel parts include the food chute, slicing table, end weight, and knife cover.

**Knife Motor:** Powerful 1/2 HP, 7 amp, 115/60/1. **Chute Motor:** Two speed DC fractional horsepower 1 amp. Both motors have permanently lubricated sealed ball bearings.

**Knife Drive:** Cross axis helical gear drive design. This maintenance free drive design is continuously lubricated ensuring quiet operation and reliable cutting performance.

**Slice Thickness:** Precision dual gear design eliminates table movement during slicing. Consistently produces tissue thin slices with a maximum slice thickness of 1 1/4" thick.

**Antimicrobial Protection:** Knobs and handles have antimicrobial protection built in, which inhibits the growth of bacteria and provides superior sanitation.

**Full Gravity Feed:** Full 45° angle feed requires less mechanical pressure. Equipped with a 3 lb. stainless steel end weight to minimize waste and hold product. Food chute handle is ergonomically designed and the end weight swings away for storage behind the chute.

**Table:** EZ-Glide™ adjustable slicing table is designed to reduce surface friction, facilitating a smooth and easy slicing stroke.

**Home Position Start:** Food chute must be pulled to the position closest to the operator to start the slicer. This forces the operator to follow proper operating procedures.

**Return to Home Chute:** Food chute automatically returns to position closest to the operator, home, when the slicer is turned off. The chute must be in the home position to start the slicer.

**Dual Arm Lift Lever:** A handle activates two large wheels, lifting the front of the unit to facilitate safe and easy cleaning underneath the slicer.

**Table Lockout:** Once the table is closed and the knife cover is removed the table cannot be opened. The table fully covers the knife's cutting edge protecting the operator during cleaning.

**Automatic Shut Off:** Slicer automatically shuts off after 10 seconds of no chute movement.

**Knife Cover Interlock:** Slicer will not operate with knife cover removed.

**Knife Ring Guard:** Permanently mounted knife ring guard covers the non-slicing portion of the knife protecting the operator from the knife's edge.

**Top Mounted Sharpener:** Metal knife sharpener is permanently mounted on the slicer. A single lever activates the stones to quickly and easily return a razor sharp cutting edge.

**Hollow Ground Knife:** 13" diameter special hardened steel alloy knife with stain resistant finish and sanitary hub provides increased cutting capacity, clean cuts, and effortless slicing. Knife's edge has a Rockwell hardness of 60-62.

**No Voltage Release:** Prevents inadvertent reactivation of slicer in the event of power or interlock interruption.

**Automatic Chute:** Chute travels 20-60 strokes per minute utilizing a separate DC motor with a heavy duty permanently lubricated chain and sprocket drive system. Chute can be quickly engaged or disengaged for manual operation with the auto engage lever.

**Touch Pad Controls:** Start/stop touch pad controls activate the knife motor. **Chute Speed:** Controlled by faster/slower touch pad controls.

**Cutting Capacity:** Width 11.6" (29.5cm), Height 9" (22.9cm), Diameter 7.5" (19cm)

**Power Indicator Light:** A readily visible red light illuminates when the knife is rotating.

**Cord & Plug:** Attached 7 foot flexible 3 wire cord with molded plug fits a grounded receptacle.

### Dimensions:

Foot Print = 14" x 21.6"  
(35.6 cm x 54.9 cm)  
Overall Length = 26.2" (66.5 cm)  
Overall Width = 22" (55.9 cm)  
Overall Height = 25.2" (64 cm)  
Freight Class: 77.5  
Net Weight: 148 lbs. (67.1 kgs.)  
Shipping Weight: 175 lbs. (79.4 kgs.)  
Shipping Dimensions:  
28"W x 25"D x 34"H  
(71.1cm x 63.5cm x 86.4cm)

### Factory Installed Options:

<b>TEFLON®</b>	Teflon® coating (coated knife, knife cover, table)
<b>FMEW</b>	Front mounted end weight
<b>PRISON</b>	Prison package
<b>MEATROOM</b>	High moisture application package
<b>LONGCHUTE</b>	15" long food chute
<b>ALUM</b>	Aluminum food chute
<b>SSK</b>	Stainless steel knife

### Accessories:

<b>1326</b>	High fence (12" x 3")
<b>1047</b>	Low fence (12" x 1 3/8")
<b>873-SET</b>	3" extension legs
<b>PS13</b>	10 lb. attachable portion control scale
<b>699-BAS</b>	Vegetable hopper
<b>SC-GLOBE</b>	Clear plastic slicer cover

*Teflon® is a registered trademark of DuPont.*

