

SECTION 2. INSTALLATION

2-1. INTRODUCTION

This section provides the installation instructions for the Henny Penny Multipurpose Holding Cabinet.

NOTICE

Installation of this unit should be performed only by a qualified service technician.



Do not puncture the skin of the unit with drills or screws as component damage or electrical shock could result.

2-2. UNPACKING

The Henny Penny Multipurpose Holding Cabinet has been tested, inspected, and expertly packed to ensure arrival at its destination in the best possible condition. The cabinet rests on cardboard pads that sit on a wooden skid. The unit is then packed inside a heavy cardboard carton with sufficient padding to withstand normal shipping treatment.

NOTICE

Any shipping damages should be noted in the presence of the delivery agent and signed prior to his or her departure.

To remove the Henny Penny Multipurpose Holding Cabinet from the carton, you should:

1. Carefully cut banding straps.
2. Lift the carton off the unit.
3. Lift the unit off the cardboard padding and skid.



Take care when moving the MPC-554 to prevent personal injury. The unit weighs 112 lbs. (50.8kg).

4. Peel off any protective covering from the exterior of the cabinet.
5. The unit is now ready for location and set up.

2-3. LOCATION

The unit should be placed on a supportive structure or shelf so the entire bottom of the unit is evenly supported, and also, where the pans can be removed without interruption and easy loading and unloading of product. For proper operation, the cabinet must be level.

Access to the controls are on the side of the unit. Do not block the controls where they are not visible or which prevents easy access by a service technician. These controls do not need to be accessed for normal operation.

2-4. ELECTRICAL CONNECTION

The data plate, located on the rear of the unit on the MPC1L & 22 and on the side of the MPC-554, specifies the correct electrical supply. The unit requires a grounded receptacle with a separate electrical line protected by a fuse or circuit breaker of the proper rating. Electrical code may also require GFCI protection.



To avoid electrical shock, the cabinet must be adequately and safely grounded (earthed) according to local electrical codes.

The units are supplied with a 9 foot (274.3 cm) power cord.

Refer to the table below for electrical ratings:

Product Number	Volts	Watts	Amps
MPC-554	120	1160	9.6
MPC-1L	120	110	.92
MPC-22	120	400	3.3

2-5. CABINET DIMENSIONS

