

# Delta® 1200

Project
Itam
Item
Quantity
CSI Section 11400
Approval
Date

### Models

Delta® 1200



#### Standard Features

- Cleans 1,200 glasses an hour
- 12" clearance allows cleaning of taller stemware, glasses and mugs
- Composite carousel conveyor prevents chipping and damage to glasses, mugs and stemware
- Low-water protectors for pump and wash heating element
- Quick-removal side panel allows tool-free access to vacuum breakers for ease of service
- Simplified, front access to all controls and chemical settings
- Efficient 1/10 hp wash pump
- Conveniently located conveyor drive motor
- · Single-switch, auto-fill operation
- Convenient, expanded chemical storage inside machine
- Three precision dispensers for detergent, rinse additive and sanitizer

- · Wash/rinse temperature gauges
- Durable 304 stainless steel construction
- Adjustable rinse control allows hot or cold water final rinses for flexible sanitizing methods
- Adjustable bullet feet
- Unit fits compactly underbar
- Removable wash/rinse arms with removable end caps on (both lower and upper) wash/ rinse arms combine for ease in cleaning
- Double-walled cabinet for quiet operation and less heat loss

## Accessories/Options

- ☐ Scrap tray
- ☐ Scale Prevention System (SPS)
- Replacement cartridges for SPS (2-pack)

## Specifications

12" (305 mm) wash clearance

Quick-removal side panel allows tool-free access to vacuum breakers

Efficient 1/10 hp wash motor

Low-water protection for wash pump and wash tank heating element

Automatic conveyor system with composite carousel to prevent damage to glasses, mugs and stemware

Cleans 1,200 glasses per hour

Gravity drain

Removable end caps on (both lower and upper) wash and rinse arms for cleaning

Three built-in precision chemical pumps for detergent, rinse additive and sanitizer

Solid-state and electromechanical components


Clockwise rotation is standard

Durable 304 stainless steel construction










#### LEGEND


Scale = 0.09:1
Unless otherwise specified, dimensions are in inches.

A = Designates the machine's rightmost side from the front

 $B = Designates \ the \ machine's \ base$ 

Adjusting the bullet feet will affect the machine's vertical dimensions





	MACHINE DIMENSIONS				GLASS	SHIPPING INFORMATION					
MODEL NO.	HEIGHT	WIDTH	DEPTH	WALL CLEARANCE	CLEARANCE	WEIGHT	CLASS	CUBE	HEIGHT	WIDTH	DEPTH
Delta® 1200	39" (991 mm)	25-1/4" (641 mm)	25-1/4" (641 mm)	2" (51 mm)	12" (305 mm)	210 lbs (95 kg)	92.5	28.2 cu. ft.	51" (1295 mm)	33" (838 mm)	29" (737 mm)

OPERATING CAPACITY/ WATER & DRAIN REQUIREMENTS					
Glasses Per Hour	1,200				
Hot Water Fill Capacity	3.0 gal (11.4 L)				
Hot Water Inlet Temperature Minimum	130°F (54.4°C)				
Minimum Cold Water Inlet Temperature	75°F (23.8°C)				
Hot Water Inlet Pressure Range (PSI)	15 to 25 PSI				
Cold Water Inlet Pressure Range (PSI)	15 to 25 PSI				
Hot (Wash) Water Consumption Rate (GPM/LPM)	0.385 gal (1.46 L)				
Cold (Rinse) Water Consumption Rate (GPM/LPM)	1.93 gal (7.3 L)				
Normal Water Consumption Rate (GPM/LPM)	2.23 gal (8.44 L)				
Incoming Waterline Size (Inches/Millimeters) IPS/MPS	1/2" (12.7 mm)				
Inlet Hot Water Line Size (Inches/Millimeters) IPS/MPS	1/2" (12.7 mm)				
Inlet Cold Water Line Size (Inches/Millimeters) IPS/MPS	1/2" (12.7 mm)				
Minimum Drainline Size (Inches/Millimeters) IPS/MPS	1-1/2" (38 mm)				

ELECTRICAL SPECIFICATIONS				
208-230V / 60HZ / 1PH	15.0 Amps			
CHEMICAL SANITIZING SPECIFICATIONS				
Sodium Hypochlorite	50 PPM			
lodiphor	12.5 PPM			
Chemical Storage Capacity (Gallon/Liter Bottles)	3.0 gal (11.4 L )			

COMPONENT SPECIFICATIONS			
Wash Pump Motor	1/10 hp		
Wash Tank Capacity	3.0 gal (11.4 L)		
Drive Motor	6.5 RPM		

HOW TO SPECIFY: Delta® 1200

SHIPPING ADDRESS 6209 North U.S. Highway 25E Gray, KY 40734

MAILING ADDRESS P.O. Box 1060 Barbourville, KY 40906 Tel: 1-888-800-5672 Fax: 606-523-1799 info@jacksonmsc.com www.jacksonmsc.com 07610-002-66-57B (02/10)

