

# SERVICE INSTRUCTIONS

www.keatingofchicago.com

**KEATING**  
OF CHICAGO, INC. ®


1-800-KEATING

## CALIBRATION MIRACLEAN® 2000 GAS GRIDDLE THERMOSTAT CALIBRATION

Calibration is not covered under warranty.

Tools: Accurate surface thermometer  
Standard screwdriver

1. Turn the exhaust system ON.
2. Turn on the griddle with thermostat set at 300°F. Allow burners to cycle on and off three times. (Approximately 60 minutes.)
3. Place accurate thermometer on surface over thermostat bulb. Use the inverted "V" on the front of the griddle plate to locate thermostat bulb. Place the surface thermometer about half way toward the back of the plate.
4. When burners cycle off, the griddle is up to temperature. If temperature is within 25°F of thermostat setting, remove knob. Loosen four screws in the thermostat dial plate. Replace knob. Reset the dial plate to match the thermometer reading.



**Thermostat calibration**  
Thermostat knob removed to reveal calibration screws.

5. Remove the knob to tighten screws on dial plate and replace the knob.

For calibration over a 25°F difference, contact a qualified service company.

### **⚠ WARNING**

**DO NOT ADJUST THE THERMOSTAT SET SCREW -  
IT VOIDS ANY WARRANTY ON PART.**