ECCO 480V 2 SPEED CONTACTOR KIT Q9-60101-191

DANGER

Disconnect oven from power before performing any conversions.

- 1. Remove top and bottom trim piece.
- 2. Open the drop down door.
- 3. Remove single screw in drop down door.
- 4. Slide control panel out until relays are exposed.
- 5. Disconnect brown wire (coming from door switch to coil of motor low relay, to coil of motor high relay, to hi-limit thermostat) off of coil of relays and label with a "1".
- 6. Disconnect red wire (coming from dual speed switch to "C" of motor low relay) from motor low relay and label with a "2".
- 7. Disconnect blue wire (coming from dual speed switch to "C" of motor high relay) from motor high relay and label with a "3".
- 8. Disconnect red wire (coming from motor to "NO" on motor high relay) from motor high relay and label with a "4".
- 9. Disconnect blue wire (coming from motor to "NO" on motor low relay) from motor low relay and label with a "5".
- 10. Disconnect red wire (coming from heat contactor to "C" of motor high relay) from motor high relay and label with a "6".
- 11. Cut black wire (coming from heat contactor to motor) and label the side from the heat contactor as "7" and the side from the motor as "8".
- 12. Remove the two old relays from the oven.
- 13. Set the new relay into the oven and use as a marker to mark out the holes.
- 14. Drill the three holes in the side panel used to secure the new relay.
- 15. Screw in the new relay.
- 16. Connect wire "1" to the coil of both the motor high and motor low relay on the "T" side of the relay (see fig. 1 and 2 for reference)
- 17. Connect wire "2" to "NC" on the motor low side of relay.
- 18. Connect wire "3" to "NC" on the motor high side of relay.
- 19. Connect wire "4" to "T3" on the motor high side of relay.
- 20. Connect wire "5" to "T3" on the motor low side of relay.
- 21. Connect wire "6" to "L3" on the motor high side of relay.
- 22. Connect wire "7" to "L1" on the motor high side of relay.
- 23. Connect wire "8" to "T1" on the motor high side of relay.
- 24. Slide control panel back into the oven and reconnect.
- 25. Test.

FIGURE 1
OLD STYLE

OL

FIGURE 2 NEW STYLE

FROM MAIN CONTACTOR HI-LIMIT DISC-STAT

