

## Insta-Therm<sup>™</sup>

Models:		
16001 16003	16005	
		<ul> <li>Standard Features:</li> <li>Heavy-duty stainless steel construction</li> <li>Contact actuated for energy savings</li> <li>Simple On/Off control</li> <li>Indicator light on cook and server side</li> <li>No pre-heat time required - heats instantly</li> <li>Quartz heating elements</li> <li>Small foot print</li> </ul>
Description: The Merco® Insta-Therm <sup>™</sup> is the perfect solution for adding the finishing touches to entrees and appetizers. No pre- heating required as <i>Insta-Therm</i> is contact actuated for energy savings and heats instantly. The menu applications are endless with <i>Insta-Therm</i> from <i>Merco</i> . Stainless Steel Construction: sturdy, sanitary, and reliable for years of dependable service. Product Opening: large 4" x 18" product opening on both sides for easy access	Indicator Lights: indicator lights on both cook and server side illuminate when elements are on. Small Footprint: allows the unit to fit in small operations without taking up valuable countertop space. Electrical Requirements: Model is available in 208 Volt, 60Hz, 2340 Watts at 11.25 Amps. NEMA 6-20P plug incuded. CE approved units available in 230 Volts, 50 Hz, 2280 Watts, at 9.91 amps. CEE 7/7 plug included.	LISTED CUD 884B US RIJ/NSF4
<b>Contact Actuated:</b> the unit activates upon contact of product resulting in energy saving for operators.	Bid Specifications for Merco <sup>®</sup> Insta- Therm <sup>™</sup> : The Insta-Therm shall be Merco model rated at watts, volts, single phase.	

Models:

16003

16005

1111 North Hadley Road P.O. Box 1229 Fort Wayne, Indiana 46801-1229 Tel 1.260.459.8200 Fax 1.260.436.0735 E mail info@mercosavory.com

www.mercosavory.com



# Dimensions:

## Insta-Therm<sup>™</sup>

## Merco<sup>®</sup> Guarantee:

*Merco* equipment is guaranteed to be free from quality problems in materials and workmanship for a period of one (1) year parts and labor from date of purchase. Quartz heating elements carry a ninety (90) day warranty against burnout (not breakage) from date of purchase of equipment.

### Merco Insta-Therm

Part #	Model #	Volts	Amps	Watts	Hz	Phase	Cord Length	Plug Type	Width	Depth	Height		
16001*	IT-18	208	11.25	2340	60	Single	6′	NEMA 6-20P	23.77″ (603.7mm)	14.04″ (356.6mm)	9.5″ (241.3mm)		
16003**	IT-18	230	9.91	2280	50	Single	6′	CEE 7/7	23.77″ (603.7mm)	14.04″ (356.6mm)	9.5″ (241.3mm)		
16005	IT-18	208	11.25	2340	60	Single	6′	NEMA 6-20P	23.77″ (603.7mm)	14.04″ (356.6mm)	9.5″ (241.3mm)		
* 50% Sta	* 50% Stand-by Energy Saving Mode. ** CE Approved unit.												

Designs and specifications subject to change without notice.

1111 North Hadley Road P.O. Box 1229 Fort Wayne, Indiana 46801-1229 Tel 1.260.459.8200 Fax 1.260.436.0735 E mail info@mercosavory.com web www.mercosavory.com ©2008 Merco LLC Printed in the U.S.A. 1187-2.5K-10/08

- F

16003

16005