## SMALL FOOTPRINT

## **BIG SPACE SAVER**

- Compact 24" unit saves valuable floor space
- Automatic defrost with forced air circulation
- Heavy-duty construction is built to last
- Front breathing design saves floor space





## 24" UNDERCOUNTER REFRIGERATOR SPECIFICATIONS

**EXTERIOR** Stainless steel, Galvanized back. **INTERIOR** Corrosion-resistant material with coved corners throughout for easy cleaning and sanitation. INSULATION Environmentally friendly foamed-in-place polyurethane insulation for maximum strength and durability. Polyurethane insulation, heavy-duty extruded aluminum frame, stainless steel exterior door panel and extra DOOR heavy-duty magnetic "Thermo Rubber" door gaskets combine to make the toughest, longest lasting door in the industry. Door liner is high impact ABS and door is easily field reversible. **SHELVES** Heavy gauge wire shelves are h<mark>and</mark> dipped, not s<mark>praye</mark>d, providing double think epoxy coating for superior durability and smooth finish. Adjustable in 1/2" increments on stainless steel pilasters. **CASTERS** Supplied with heavy-duty casters, (two with locks) threaded to Rivnuts, secured to a 12 gauge steel base to ensure years of trouble free operation. CFC-free refrigerant. Hermetically sealed, high efficiency, self contained refrigeration system features automatic REFRIGERATION defrost and forced air circulation. Evaporator coil positioned for uniform air distribution and optimum cooling. Ad<mark>justable temperature control and</mark> built-in temp<mark>eratur</mark>e indicator standard. Automatic condensate evaporator means no plumbing or floor drains. **ELECTRICAL** Standard as 115 volt, 60Hz, single phase operation. 8 foot, 3-wire power cord with NEMA 5-15 plug. Available in 230 volt, 50 Hz, single phase. LISTINGS c(U.S. and Canada), NSF International. One year parts and labor warranty on cabinet and refrigeration system. Five year warranty on compressor. WARRANTY **ACCESSORIES** Mobility Kit, Glass Door.

MODEL	LENGTH	DEPTH	HEIGHT	STORAGE CAPACITY	SHELVES	SHELF AREA	COMPRESSOR	AMPS	WEIGHT	
SKR24	24"	25"	32"	4.4 cu. ft.	2	5.9 sq. ft.	1/5 hp	2.2	155 lbs	





Specifications subject to change without notice.


Dimensions in inches and centimeters

MODEL SKR24











1600 Xenium Lane North Minneapolis, MN 55441-3787 Phone (763) 923-2441 Fax (763) 553-1209 www.silverking.com