## COMPACT FREEZER

## AT YOUR FINGERTIPS

- Low temperature storage where you need it.
- Great on a counter or on a shelf.
- High luster stainless steel exterior.
- Extra heavy-duty magnetic door gasket.





## SHELF FREEZER SPECIFICATIONS

MODEL SKSF EXTERIOR Stainless steel, Galvanized back.

INTERIOR Corrosion-resistant material with coved corners throughout for fast, easy, cleaning and sanitation.

INSULATION Environmentally friendly foamed-in-place polyurethane insulation for maximum insulation, strength and durability.

DOOR Polyurethane insulation, extruded aluminum frame, stainless steel exterior door panel and extra heavy-duty magnetic "Thermo Rubber" door gasket combine to make the toughest, longest lasting door in the industry.

SHELF Heavy gauge wire shelf is hand-dipped, to provide double layer epoxy coating for superior durability and smooth

handling. Adjustable 1/2" increments on stainless steel pilasters.

REFRIGERATION CFC-free, R401a refrigerant, hermetically sealed, high efficiency, self contained refrigeration system features

automatic defrost and forced air circulation. Adjustable temperature control and built-in temperature indicator

standard. Automatic condensate evaporator means no plumbing is required.

ELECTRICAL Standard 115 volt, 60Hz, single phase. 8 foot, 3-wire power cord with NEMA 5-15 plug.

LISTINGS (U.S. and Canada), NSF International


WARRANTY One year materials and workmanship warranty on cabinet and refrigeration system. Five year warranty on


compressor.

MODEL	LENGTH	DEPTH	HEIGHT	STORAGE CAPACITY	AMPS	COMPRESSOR	SHIPPING WEIGHT
SKSF	271/2"	327/8"	20"	4.4 cu. ft.	5.3	1/3 hp	130lbs



(numbers in parenthesis are centimeters)





FRONT VIEW



1600 Xenium Lane North Minneapolis, MN 55441-3787 Phone (763) 923-2441 Fax (763) 553-1209 www.silverking.com