

DEEP WORKTOP REFRIGERATORS

Model	Doors/ Drawers	Cu. Ft.	# of Shelves	HP	Amps	Crated Weight	Cabinet Dimensions		
							L	D†	H*
TWT-44	1/0	11.4	2	1/5	5.1	285	44 ¹ / ₂ x 32 ³ / ₈ x 33 ³ / ₈		
TWT-60-32	2/0	15.9	4	1/5	5.1	360	60 ¹ / ₄ x 32 ³ / ₈ x 33 ³ / ₈		
TWT-67	2/0	20.6	4	1/5	5.1	380	67 ¹ / ₄ x 32 ³ / ₈ x 33 ³ / ₈		
TWT-93	3/0	30.9	6	1/2	9.7	535	93 ¹ / ₄ x 32 ³ / ₈ x 33 ³ / ₈		
TWT-119	4/0	43.9	8	1/2	12.0	660	119 ¹ / ₄ x 32 ³ / ₈ x 33 ³ / ₈		
DRAWERED									
TWT-44D-2	0/2	11.4	N/A	1/5	5.1	285	44 ¹ / ₂ x 32 ³ / ₈ x 33 ³ / ₈		
TWT-60-32D-2	1/2	15.9	2	1/5	5.1	395	60 ¹ / ₄ x 32 ³ / ₈ x 33 ³ / ₈		
TWT-67D-2	1/2	20.6	2	1/5	5.1	430	67 ¹ / ₄ x 32 ³ / ₈ x 33 ³ / ₈		
TWT-67D-4	0/4	20.6	N/A	1/5	5.1	465	67 ¹ / ₄ x 32 ³ / ₈ x 33 ³ / ₈		
TWT-93D-2	2/2	30.9	4	1/2	9.7	610	93 ¹ / ₄ x 32 ³ / ₈ x 33 ³ / ₈		
TWT-93D-4	1/4	30.9	2	1/2	9.7	610	93 ¹ / ₄ x 32 ³ / ₈ x 33 ³ / ₈		
TWT-93D-6	0/6	30.9	N/A	1/2	9.7	610	93 ¹ / ₄ x 32 ³ / ₈ x 33 ³ / ₈		
TWT-119D-2	3/2	43.9	6	1/2	12.0	N/A	119 ¹ / ₄ x 32 ³ / ₈ x 33 ³ / ₈		
TWT-119D-4	2/4	43.9	4	1/2	12.0	725	119 ¹ / ₄ x 32 ³ / ₈ x 33 ³ / ₈		
TWT-119D-6	1/6	43.9	2	1/2	12.0	N/A	119 ¹ / ₄ x 32 ³ / ₈ x 33 ³ / ₈		
TWT-119D-8	0/8	43.9	N/A	1/2	12.0	810	119 ¹ / ₄ x 32 ³ / ₈ x 33 ³ / ₈		

† Depth does not include 1" for rear bumpers or 1/4" for front bumper.

* Height does not include 6¹/₄" for castors or 6" for optional legs.

note: Door/drawer combination cabinets require customer to designate door/drawer orientation.



TWT-44



TWT-67



TWT-93D-6

DEEP WORKTOP FREEZERS

Model	Doors	Cu. Ft.	# of Shelves	HP	Amps	Crated Weight	Cabinet Dimensions		
							L	D†	H*
TWT-44F	1	11.4	2	1/2	10.2	310	44 ¹ / ₂ x 32 ³ / ₈ x 33 ³ / ₈		
TWT-60-32F	2	15.9	4	1/2	10.4	370	60 ¹ / ₄ x 32 ³ / ₈ x 33 ³ / ₈		
TWT-67F	2	20.6	4	3/4	11.7	405	67 ¹ / ₄ x 32 ³ / ₈ x 33 ³ / ₈		
TWT-93F	3	30.9	6	3/4	10.2	545	93 ¹ / ₄ x 32 ³ / ₈ x 33 ³ / ₈		

† Depth does not include 1" for rear bumpers or 1/4" for front bumper.

* Height does not include 6¹/₄" for castors or 6" for optional legs.

DEEP TWT MODELS
Heavy, 16 Gauge Tops
All TWT-44 models
All TWT-60-32 models
All TWT-67 models
All TWT-93 models

Heavy Duty Package: 20 gauge door, 20 gauge sides, 20 gauge back, 16 gauge top & stainless interior
TWT-44HD / TWT-44F-HD
TWT-60-32HD / TWT-60-32F-HD
TWT-67HD / TWT-67F-HD
TWT-93HD / TWT-93F-HD

FEATURES/BENEFITS

- Oversized, environmentally friendly refrigeration system (refrigerators: 134A / freezers: R404A).
- Refrigerator holds 33°F to 38°F temperature; freezer holds -10°F.
- Automatic defrost system on freezer models time-initiated, time-terminated.
- 360° circular airflow for uniform product cooling.
- All stainless steel front, top and sides.
- Interior - attractive, NSF approved, white aluminum sides and top, coved corners and 300 series stainless steel floor.
- Aluminum finished back.
- Work surface 36" high.
- Front breathing.
- Features the combined advantage of convenient worktop prep space with deeper refrigerated storage.
- Recessed handles.
- Adjustable, heavy duty, PVC coated wire shelves (not available in drawered sections).
- Foamed-in-place high density polyurethane insulation (CFC free).
- 5" diameter castors standard equipment (legs available).
- Doors swing within cabinet dimensions.
- Self-contained system.
- Door models accommodate half bun tray rack; applies to only one door of TWT-60-32 (18" x 26" sheet pan) not included.
- Heavy, 16 gauge tops available (excludes -119 models) upcharge applies.
- Available with optional 3" diameter castors.

Drawered Models

- Accommodates two, 12"L x 20"W x 8"D full size pans or four 1/2 pans or six 1/3 pans per drawer. Pans not included.
- Door/drawer combination models require customer to designate door/drawer orientation.

Remote cabinets available 14% off list (condensing units supplied by others; system comes standard with 404A expansion valve and requires R404A refrigerant). Consult factory technical service dept. for BTU information.